



ATTACHMENTS



CONTENTS

Universal Mini Attachments.....	3
<u>Color Key.....</u>	4
Buckets.....	5
Augers.....	10
Soil Mowers.....	13
Grapples.....	16
Dozer Blades.....	20
Trenchers.....	22
Plows.....	24
Forks.....	26
Cutters.....	28
Snow Tools.....	30
Breakers.....	32
Misc. Attachments.....	34
 Full-Sized Attachments.....	 36
<u>Color Key.....</u>	37
Buckets.....	38
Grapples.....	40
Trenchers.....	41
Forks.....	43
 Color Key.....	 45



UNIVERSAL MINI ATTACHMENTS



COLOR KEY

 **COMPATIBLE**  **COMPATIBLE BUT NOT RECOMMENDED**  **NOT AUTHORIZED**

COMPATIBLE: The attachment is compatible with the associated base unit. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

COMPATIBLE BUT NOT RECOMMENDED: The attachment is technically compatible but not recommended for combined use with the associated base unit. Functionality, reliability or performance may be limited; damage to or excess wear and tear on the attachment or base unit is possible. Note that use of attachments that are not recommended by Vermeer and that (in the sole judgment of Vermeer) amounts to abnormal use, misuse or negligence will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

NOT AUTHORIZED: The attachment is not authorized for use with the associated base unit. Combined use may be technically infeasible or pose unacceptable risk of harm to property or persons. Never operate these attachments and base units in combination. Note that use of these attachments, in addition to being unsafe, will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.



BUCKETS





BUCKETS

SPECIFICATIONS

STANDARD BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
UMA1000	BERLON HD LOW PROFILE BUCKET – 36 in WIDE	MIB-36	36 in (91 cm)	37.5 in (95.3 cm)	20 in (50 cm)	27 in (69 cm)	175 lb (79.4 kg)	7.5 ft ³ (.212 m ³)
UMA1005	BERLON HD LOW PROFILE BUCKET – 42 in WIDE	MIB-42	42 in (110 cm)	43.5 in (110 cm)	20 in (50 cm)	27 in (69 cm)	195 lb (88.5 kg)	8.8 ft ³ (.249 m ³)
UMA1010	BERLON HD LOW PROFILE BUCKET – 48 in WIDE	MIB-48	48 in (120 cm)	49.5 in (126 cm)	20 in (50 cm)	27 in (69 cm)	215 lb (97.5 kg)	10 ft ³ (.283 m ³)
UMA1015	BERLON HD LOW PROFILE BUCKET – 54 in WIDE	MIB-54	54 in (140 cm)	55.5 in (141 cm)	20 in (50 cm)	27 in (69 cm)	235 lb (107 kg)	11.3 ft ³ (.320 m ³)

TOOTH BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
UMA1020	BERLON HD TOOTH BUCKET – 36 in WIDE	MIB-36WET2	36 in (91 cm)	37.5 in (95.3 cm)	20 in (50 cm)	27 in (69 cm)	187 lb (84.8 kg)	7.5 ft ³ (.212 m ³)
UMA1025	BERLON HD TOOTH BUCKET – 42 in WIDE	MIB-42WET2	42 in (110 cm)	43.5 in (110 cm)	20 in (50 cm)	27 in (69 cm)	207 lb (93.9 kg)	8.8 ft ³ (.249 m ³)
UMA1030	BERLON HD TOOTH BUCKET – 48 in WIDE	MIB-48WET2	48 in (120 cm)	49.5 in (126 cm)	20 in (50 cm)	27 in (69 cm)	227 lb (103 kg)	10 ft ³ (.283 m ³)
UMA1035	BERLON HD TOOTH BUCKET – 54 in WIDE	MIB-54WET2	54 in (140 cm)	55.5 in (141 cm)	20 in (50 cm)	27 in (69 cm)	257 lb (117 kg)	11.3 ft ³ (.320 m ³)



BUCKETS

SPECIFICATIONS

HIGH VOLUME BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
UMA1040	BERLON MULCH BUCKET – 48 in WIDE	MISLMB-48	48 in (120 cm)	49 in (126 cm)	29 in (74 cm)	39 in (99 cm)	440 lb (200 kg)	22 ft ³ (.623 m ³)
UMA1045	BERLON MULCH BUCKET – 54 in WIDE	MISLMB-54	54 in (140 cm)	55.5 in (141 cm)	29 in (74 cm)	39 in (99 cm)	465 lb (211 kg)	24.75 ft ³ (.701 m ³)
UMA1050	BERLON MULCH BUCKET – 60 in WIDE	MISLMB-60	60 in (153 cm)	61.5 in (156 cm)	29 in (74 cm)	39 in (99 cm)	490 lb (220 kg)	27.5 ft ³ (.779 m ³)
UMA1080	BERLON MULCH BUCKET – 34.5 in WIDE	121153	NA	34.5 in (87.6 cm)	NA	NA	239 lb (108 kg)	6 ft ³ (.170 m ³)

MISC. BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
UMA1071	UDMP48 – HIGH DUMP BUCKET – 48 in WIDE	NA	NA	48 in (120 cm)	27.5 in (69.9 cm)	39 in (99 cm)	530 lb (240 kg)	11.6 ft ³ (.328 m ³)
UMA1074	BRADCO 4-IN-1 BUCKET – 38 in WIDE	18076-X	NA	38 in (97 cm)	25 in (64 cm)	28 in (71 cm)	250 lb (110 kg)	4.5 ft ³ (.127 m ³)
UMA1075	BRADCO 4-IN-1 BUCKET – 42 in WIDE	17767-X	NA	42 in (110 cm)	25 in (64 cm)	28 in (71 cm)	265 lb (120 kg)	5 ft ³ (.142 m ³)
UMA1085	BRADCO ROCK BUCKET – 42 in WIDE	19695-X	NA	42 in (110 cm)	15 in (38 cm)	25 in (64 cm)	180 lb (82 kg)	NA
UMA1087	BRADCO POWER SHOVEL	2000867-X	NA	25 in (64 cm)	25 in (64 cm)	47 in (120 cm)	163 lb (73.9 kg)	NA



BUCKETS

MINI SKID STEERS ATTACHMENT COMPATIBILITY

STANDARD BUCKETS

	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1000	X	X	X	X	•
UMA1005	X	X	X	X	X
UMA1010	•	•	X	X	X
UMA1015	•	•	•	X	X

TOOTH BUCKETS

UMA1020	X	X	X	X	•
UMA1025	X	X	X	X	X
UMA1030	•	•	X	X	X
UMA1035		•	•	X	X

HIGH VOLUME BUCKETS

UMA1040			X	X	X
UMA1045			X	X	X
UMA1050			•	X	X
UMA1080	X	X	X		

MISC. BUCKETS

UMA1071			X	X	X
UMA1074	X	X	X		
UMA1075	X	X	X		
UMA1085	X	X	X		
UMA1087	•	•	X	X	X

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



BUCKETS

ARTICULATED LOADERS ATTACHMENT COMPATIBILITY

STANDARD BUCKETS

	ATX530	ATX720	ATX850	ATX960
UMA1000	•	•	•	
UMA1005	X	X	X	
UMA1010	X	X	X	
UMA1015	X	X	X	

TOOTH BUCKETS

UMA1020	•	•	•	
UMA1025	X	X	•	
UMA1030	X	X	X	
UMA1035	X	X	X	

HIGH VOLUME BUCKETS

UMA1040	X	X	X	
UMA1045	X	X	X	
UMA1050	•	X	X	
UMA1080	X	X		

MISC. BUCKETS

UMA1071	X	X	X	
UMA1074	X	X		
UMA1075	X	X		
UMA1085	X	X		
UMA1087	X	X	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



AUGERS





AUGERS

SPECIFICATIONS

AUGERS – ATTACHMENTS

Price Book	Description	Industry Part Number	Weight	Max Torque	Max Pressure	Max Flow
UMA1100	MCMILLEN AUGER DRIVE – HIGH TORQUE	24384-X	150 lb (68 kg)	1,998 ft-lb (2,709 Nm)	3,000 psi (20 MPa)	25 gpm (95 L/min)
UMA1105	MCMILLEN AUGER DRIVE – HIGH SPEED	24347-X	150 lb (68 kg)	1,500 ft-lb (2,000 Nm)	3,000 psi (20 MPa)	25 gpm (95 L/min)

AUGERS – EXTENSION

Price Book	Description	Industry Part Number	Weight	Length
UMA1160	MCMILLEN AUGER EXTENSION – 12 in	24389	22 lb (10 kg)	12 in (30 cm)

AUGERS – BITS

Price Book	Description	Industry Part Number	Weight	Width	Length
UMA1110	MCMILLEN AUGER BIT – 6 in	24380	42 lb (19 kg)	6 in (15 cm)	48 in (120 cm)
UMA1115	MCMILLEN AUGER BIT – 9 in	24381	86 lb (39 kg)	9 in (20 cm)	48 in (120 cm)
UMA1116	PENGO AUGER BIT – 9 in SRR ROCK	PEN102472	110 lb (50 kg)	9 in (20 cm)	48 in (120 cm)
UMA1120	MCMILLEN AUGER BIT – 12 in	24383	120 lb (54 kg)	12 in (30 cm)	48 in (120 cm)
UMA1125	MCMILLEN AUGER BIT – 15 in	24384	140 lb (64 kg)	15 in (38 cm)	48 in (120 cm)
UMA1130	MCMILLEN AUGER BIT – 18 in	24385	160 lb (73 kg)	18 in (46 cm)	48 in (120 cm)
UMA1135	MCMILLEN AUGER BIT – 24 in	24386	278 lb (126 kg)	24 in (61 cm)	48 in (120 cm)
UMA1140	MCMILLEN AUGER BIT – 30 in	24387	325 lb (147 kg)	30 in (80 cm)	48 in (120 cm)
UMA1145	MCMILLEN AUGER BIT – 36 in	24061	443 lb (201 kg)	36 in (91 cm)	48 in (120 cm)
UMA1150	MCMILLEN AUGER BIT – 30 in HTF TREE	24338	264 lb (120 kg)	30 in (80 cm)	48 in (120 cm)
UMA1155	MCMILLEN AUGER BIT – 36 in HTF TREE	24060	349 lb (158 kg)	36 in (91 cm)	48 in (120 cm)



AUGERS

ATTACHMENT COMPATIBILITY

AUGERS – MINI SKID STEERS

	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1100	X	X	X	X	X
UMA1105	X	X	X	X	X

AUGERS – COMPACT ARTICULATED LOADERS

	ATX530	ATX720	ATX850	ATX960
UMA1100	X	•	X	
UMA1105	X	•	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



SOIL MOWERS





SOIL MOWERS

SPECIFICATIONS

SOIL MOWERS							
Price Book	Description	Industry Part Number	Width	Working Depth	Max Flow	Max Pressure	Weight
MSSA357	ROTADAIRON SOIL RENOVATOR STH-36 (STEC)	STH-36	38 in (97 cm)	5.5 in (14 cm)	15.8 gpm (60 L/min)	3,625 psi (25 MPa)	584 lb (265 kg)
MSSA305	TILLER – 40 in W X 4.5 in DEPTH	B17766	40 in (100 cm)	4.5 in (10 cm)	16 gpm (61 L/min)	3,000 psi (20 MPa)	335 lb (152 kg)

Price Book	Description	Industry Part Number	Width	Max Flow	Carrier Pressure	Weight	Number of Knives
MSSA359	ROTADAIRON BRUSH MOWER/ MULCHER BRD50 (STEC)	BRD50	56 in (140 cm)	15.8 gpm (60 L/min)	2,900 psi (20 MPa)	608 lb (276 kg)	76

Price Book	Description	Industry Part Number	Width	Working Width	Max Flow	Max Pressure	Angle Roll Degree	Weight
UMA1300	HARLEY RAKE -D4M – MANUAL	22748M- 0961-X	55.4 in (140 cm)	48 in (120 cm)	15 gpm (57 L/min)	3,000 psi (20 MPa)	20	365 lb (166 kg)
UMA1305	HARLEY RAKE -D4H3 – DUAL HYD	22748H3- 0961-X	55.4 in (140 cm)	48 in (120 cm)	15 gpm (57 L/min)	3,000 psi (20 MPa)	20	380 lb (170 kg)



SOIL MOWERS

ATTACHMENT COMPATIBILITY

SOIL MOWERS – MINI SKID STEERS

	CTX50	S450TX	S925TX	CTX100	CTX160
MSSA357			X	X	X
MSSA305	•	•	X	X	X
MSSA359			X	X	X
UMA1300	•	•	X	X	X
UMA1305	•	•	X	X	X

SOIL MOWERS – COMPACT ARTICULATED LOADERS

	ATX530	ATX720	ATX850	ATX960
MSSA357	X	X	X	
MSSA305	X	•	X	
MSSA359	X	X	X	
UMA1300	X	X	X	
UMA1305	•	•	•	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



GRAPPLES





GRAPPLES

SPECIFICATIONS

GRAPPLES							
Price Book	Description	Industry Part Number	Weight	Width	Claw Opening	Max Capacity	Hydraulic Cylinder
UMA1423	VERMEER BRUSH GRAPPLE – UBG36	NA	355 lb (162 kg)	36 in (91 cm)	42 in (107 cm)	1,245 lb (564 kg)	3,000 psi (20 MPa)
UMA1426	VERMEER BRUSH GRAPPLE – UBG42	NA	365 lb (166 kg)	42 in (110 cm)	42 in (110 cm)	1,235 lb (560 kg)	3,000 psi (20 MPa)
UMA1429	VERMEER BRUSH GRAPPLE – UBG48	NA	415 lb (189 kg)	48 in (120 cm)	42 in (110 cm)	1,185 lb (537 kg)	3,000 psi (20 MPa)
UMA1432	VERMEER BRUSH GRAPPLE – UBG54	NA	425 lb (193 kg)	54 in (138 cm)	42 in (110 cm)	1,175 lb (532 kg)	3,000 psi (20 MPa)
UMA1433	VERMEER BRUSH GRAPPLE DUAL – UBG54D	NA	545 lb (248 kg)	54 in (138 cm)	42 in (110 cm)	1,055 lb (478 kg)	3,000 psi (20 MPa)
UMA1442	BRADCO SCRAP GRAPPLE BUCKET – 36 in WIDE	107480-X	260 lb (120 kg)	36 in (91 cm)	29 in (74 cm)	NA	3,000 psi (20 MPa)
UMA1443	BRADCO SCRAP GRAPPLE BUCKET – 42 in WIDE	107481-X	280 lb (130 kg)	42 in (110 cm)	29 in (74 cm)	NA	3,000 psi (20 MPa)
UMA1420	BERLON FORESTRY CLAW – 60 in	MIFC2	261 lb (118 kg)	NA	60 in (153 cm)	2,000 lb (900 kg)	3,000 psi (20 MPa)
UMA1400	VERMEER ULG46 – FIXED LOG GRAPPLE	NA	440 lb (200 kg)	NA	46 in (117 cm)	1,500 lb (600 kg)	3,000 psi (20 MPa)
UMA1405	VERMEER USLG46 – SWIVEL LOG GRAPPLE	NA	375 lb (170 kg)	NA	46 in (117 cm)	1,500 lb (600 kg)	3,000 psi (20 MPa)
UMA1410	VERMEER URLG46 – HYD ROTATING LOG GRAPPLE	NA	400 lb (200 kg)	NA	46 in (117 cm)	1,500 lb (600 kg)	3,000 psi (20 MPa)



GRAPPLES

SPECIFICATIONS

GRAPPLES							
Price Book	Description	Industry Part Number	Weight	Width	Claw Opening	Max Capacity	Hydraulic Cylinder
UMA1413	VERMEER ROOT RAKE GRAPPLE – URRG42	NA	395 lb (180 kg)	42 in (107 cm)	36 in (92 cm)	1,205 lb (547 kg)	3,000 psi (20 MPa)
UMA1417	VERMEER ROOT RAKE GRAPPLE – URRG48	NA	455 lb (207 kg)	48 in (122 cm)	36 in (92 cm)	1,145 lb (520 kg)	3,000 psi (20 MPa)
UMA1419	VERMEER ROOT RAKE GRAPPLE – URRG54	NA	480 lb (218 kg)	54 in (138 cm)	36 in (92 cm)	1,120 lb (508 kg)	3,000 psi (20 MPa)



GRAPPLES

ATTACHMENT COMPATIBILITY

GRAPPLES – MINI SKID STEERS

	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1423	X	X	•	•	•
UMA1426	•	•	X	X	X
UMA1429			X	X	X
UMA1432			•	•	X
UMA1433			•	•	X
UMA1442	X	X	X		
UMA1443	X	X	X		
UMA1420	X	X	X	X	X
UMA1400		•	X	X	X
UMA1405	X	X	X	X	X
UMA1410	X	X	X	X	X
UMA1413	•	•	X	X	X
UMA1417			X	X	X
UMA1419			X	X	X

SOIL MOWERS – COMPACT ARTICULATED LOADERS

	ATX530	ATX720	ATX850	ATX960
UMA1423	•	•	•	
UMA1426	X	X	X	
UMA1429	X	X	X	
UMA1432	•	•	X	
UMA1433	•	•	X	
UMA1442				
UMA1443				
UMA1420	X	X	X	
UMA1400	X	X	X	
UMA1405	X	X	X	
UMA1410	•	•	•	
UMA1413	X	X	X	
UMA1417	X	X	X	
UMA1419	•	•	X	



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



DOZER BLADES





DOZER BLADES

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

DOZER BLADES								
Price Book	Description	Industry Part Number	Weight	Width	Height	Angle (Left to Right)	Tilt (Left to Right)	Hydraulic Cylinder
UMA1250	BRADCO HYD DOZER BLADE – 46 in WIDE	104672-X	257 lb (117 kg)	47 in (120 cm)	17 in (43 cm)	30	0	3,000 psi (20 MPa)
UMA1255	BRADCO HYD DOZER BLADE W/TILT – 46 in WIDE	104571-X	257 lb (117 kg)	47 in (120 cm)	17 in (43 cm)	30	6	3,000 psi (20 MPa)
UMA1260	BRADCO HYD DOZER BLADE W/TILT – 67 in WIDE	105672-X	310 lb (140 kg)	67 in (170 cm)	17 in (43 cm)	30	6	3,000 psi (20 MPa)

DOZER BLADES – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1250	X	X	X	X	X
UMA1255	X	X	X	X	X
UMA1260	•	•	X	X	X

DOZER BLADES – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
UMA1250	X	X	X	
UMA1255	X	X	X	
UMA1260	•	X	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



TRENCHERS





TRENCHERS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

TRENCHERS							
Price Book	Description	Industry Part Number	Max Weight	Max Trench Depth	Max Trench Width	Max Flow	Max Pressure
UMA1450	VERMEER TRENCHER ATTACHMENT – UTR48	NA	640 lb (290 kg)	48 in (120 cm)	8 in (20 cm)	20 gpm (80 L/min)	3,100 psi (21 MPa)
MSSA500	VERMEER TRENCHER ATTACHMENT – STR48	NA	520 lb (240 kg)	48 in (120 cm)	8 in (20 cm)	16.5 gpm (62.5 L/min)	3,000 psi (20 MPa)

TRENCHERS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
MSSA500	•		X	X	X
UMA1450	•	•	X	X	X

TRENCHERS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
MSSA500	X	•		
UMA1450	X	•	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



PLOWS





PLOWS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

PLOWS								
Price Book	Description	Industry Part Number	Weight	Max Plow Depth	Max Product Diameter Plowed	Max Product Diameter Pulled	Max Flow	Max Pressure
MSSA600	VERMEER SVP18 – VIBRATORY PLOW ATTACHMENT	NA	340 lb (150 kg)	12 in (30 cm)	.75 in (19 mm)	1.5 in (3.8 cm)	16.5 gpm (62.5 L/min)	3,100 psi (21 MPa)

PLOWS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
MSSA600	•	•	X	X	X

PLOWS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
MSSA600	X	•		

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



FORKS





FORKS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

FORKS						
Price Book	Description	Industry Part Number	Weight	Fork Length	Frame Width	Rated Capacity
UMA1500	BERLON PALLET FORKS AND FRAME – 36 in WIDE	MIPFF-36	260 lb (120 kg)	36 in (91 cm)	30.5 in (77.5 cm)	3,500 lb (1,600 kg)
UMA1505	BERLON PALLET FORKS AND FRAME – 42 in WIDE	MIPFF-42	270 lb (122.5 kg)	42 in (110 cm)	30.5 in (77.5 cm)	3,500 lb (1,600 kg)
UMA1510	BERLON PALLET FORKS AND FRAME – 48 in WIDE	MIPFF-48	280 lb (127 kg)	48 in (120 cm)	30.5 in (77.5 cm)	3,500 lb (1,600 kg)

FORKS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1500	X	X	X	X	•
UMA1505	X	X	X	X	X
UMA1510	•	X	X	X	X

FORKS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
UMA1500	•	•	•	
UMA1505	X	•	•	
UMA1510	X	•	•	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



CUTTERS





CUTTERS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

CUTTERS									
Price Book	Description	Industry Part Number	Weight	Max Cutting Depth	Max Cutting Width	Max Cutting Height	Min Flow	Max Flow	Max Pressure
MSSA715	VERMEER ROOT CUTTER – RC14	NA	550 lb (250 kg)	14 in (36 cm)	2.5 in (6.4 cm)	NA	NA	16.5 gpm (62.5 L/min)	3,045 psi (21 MPa)
UMA1700	VERMEER STUMP CUTTER – USCA30	NA	660 lb (300 kg)	12 in (30 cm)	36 in (91 cm)	24.5 in (62 cm)	12 gpm (45 L/min)	17 gpm (64 L/min)	3,100 psi (22 MPa)

CUTTERS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
MSSA715	•		X	X	X
UMA1700			•	X	X

CUTTERS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
MSSA715	X	X		
UMA1700				

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



SNOW TOOLS





SNOW TOOLS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

SNOW TOOLS					
Price Book	Description	Industry Part Number	Weight	Width	Height
UMA1615	BERLON SNOW BLADE – 48 in WIDE	MISBLD-4	318 lb (144 kg)	48 in (120 cm)	22 in (56 cm)
UMA1620	BERLON SNOW BLADE – 66 in WIDE	MISBLD-5.5	353 lb (160 kg)	66 in (170 cm)	22 in (56 cm)
UMA1630	BERLON SNOW PUSHER – 60 in WIDE	MISPLP-5	725 lb (329 kg)	60 in (153 cm)	34 in (86 cm)

SNOW TOOLS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1615	•	•	X	X	X
UMA1620	•	•	X	X	X
UMA1630			•	X	X

SNOW TOOLS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
UMA1615	X	X	X	
UMA1620	X	X	X	
UMA1620	•	•	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



BREAKERS





BREAKERS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

BREAKERS							
Price Book	Description	Industry Part Number	Weight	Max Boring Diameter	Max Torque	Max Energy	Steel Diameter
MSSA605	HYDRAULIC BORING ATTACHMENT (MCL)	MC4500MS	115 lb (52.2 kg)	4.5 in (11 cm)	530 ft-lb (720 Nm)	NA	NA
MSSA700	VERMEER HYDRAULIC BREAKER ATTACHMENT	HP200 FS	250 lb (110 kg)	NA	NA	200 lb-ft (27.7 kg-m)	1.8 in (4.6 cm)

BREAKERS – MINI SKID STEERS					
	CTX50	S450TX	S925TX	CTX100	CTX160
MSSA605	•	•	X	X	X
MSSA700	•	•	X	X	X

BREAKERS – COMPACT ARTICULATED LOADERS				
	ATX530	ATX720	ATX850	ATX960
MSSA605	X	•	X	
MSSA700	X	•	X	

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



MISC. PRODUCTS





MISC. PRODUCTS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

MISC.

Price Book	Description	Industry Part Number	Weight	Tilt	Width	Tine Length	Fork Range of Motion	Max Flow	Max Pressure
UMA1210	BRADCO TREE FORK	19938-X	145 lb (65.8 kg)	NA	25 in (64 cm)	33 in (84 cm)	23 in (58 cm)	NA	3,000 psi (20 MPa)
UMA1225	BRADCO MINI TILT	100145-X	94 lb (43 kg)	18	NA	NA	NA	NA	NA
UMA1275	SWEEPSTER ROTARY BROOM – MANUAL	22641MM-0961-X	340 lb (150 kg)	NA	42 in (110 cm)	NA	NA	16 gpm (61 L/min)	3,000 psi (20 MPa)

MISC.

Price Book	Description	Industry Part Number	Bit Diameter	Maximum Flow	Maximum Pressure	Weight	Max Torque
NA	FECON STUMP SCREW – SHX12	SHX12	12 in (30 cm)	10 gpm – 20 gpm (40 L/min – 80 L/min)	3,000 psi (20 MPa)	400 lb (200 kg)	4,000 ft-lb (5,000 Nm)

MISC. – MINI SKID STEERS

	CTX50	S450TX	S925TX	CTX100	CTX160
UMA1210	X	X	X	X	X
UMA1225	X	X	X	X	X
UMA1275	X	X	X	X	X
SHX12			X	X	X

MISC. – COMPACT ARTICULATED LOADERS

	ATX530	ATX720	ATX850	ATX960
UMA1210	X	•	X	
UMA1225	X	•	X	
UMA1275	X	•	X	
SHX12				

X COMPATIBLE
 • COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



***FULL-SIZE
ATTACHMENTS***



COLOR KEY

 **COMPATIBLE**  **COMPATIBLE BUT NOT RECOMMENDED**  **NOT AUTHORIZED**

COMPATIBLE: The attachment is compatible with the associated base unit. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

COMPATIBLE BUT NOT RECOMMENDED: The attachment is technically compatible but not recommended for combined use with the associated base unit. Functionality, reliability or performance may be limited; damage to or excess wear and tear on the attachment or base unit is possible. Note that use of attachments that are not recommended by Vermeer and that (in the sole judgment of Vermeer) amounts to abnormal use, misuse or negligence will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

NOT AUTHORIZED: The attachment is not authorized for use with the associated base unit. Combined use may be technically infeasible or pose unacceptable risk of harm to property or persons. Never operate these attachments and base units in combination. Note that use of these attachments, in addition to being unsafe, will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.



BUCKETS

SPECIFICATIONS

UTILITY BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight
FSA1000	BERLON UTILITY BUCKET – 48 in	UT – 48	48 in (120 cm)	49.5 in (126 cm)	21 in (53 cm)	33 in (84 cm)	353 lb (160 kg)
FSA1005	BERLON UTILITY BUCKET – 54 in	UT – 54	54 in (140 cm)	55.5 in (141 cm)	21 in (53 cm)	33 in (84 cm)	385 lb (175 kg)
FSA1010	BERLON UTILITY BUCKET – 60 in	UT – 60	60 in (153 cm)	61.5 in (156 cm)	21 in (53 cm)	33 in (84 cm)	406 lb (184 kg)
FSA1015	BERLON UTILITY BUCKET – 66 in	UT – 66	66 in (170 cm)	67.5 in (171 cm)	21 in (53 cm)	33 in (84 cm)	431 lb (195 kg)

TOOTH BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
FSA1020	BERLON HD TOOTH BUCKET – 48 in WIDE	UT-48WET2	48 in (120 cm)	49.5 in (126 cm)	21 in (53 cm)	33 in (84 cm)	360 lb (160 kg)	12.8 ft ³ (.362 m ³)
FSA1025	BERLON HD TOOTH BUCKET – 54 in WIDE	UT-54WET2	54 in (140 cm)	55.5 in (141 cm)	21 in (53 cm)	33 in (84 cm)	400 lb (181 kg)	14.4 ft ³ (.408 m ³)
FSA1030	BERLON HD TOOTH BUCKET – 60 in WIDE	UT-60WET2	60 in (153 cm)	61.5 in (156 cm)	21 in (53 cm)	33 in (84 cm)	426 lb (193 kg)	16 ft ³ (.453 m ³)
FSA1035	BERLON HD TOOTH BUCKET – 66 in WIDE	UT-66WET2	66 in (170 cm)	67.5 in (171 cm)	21 in (53 cm)	33 in (84 cm)	451 lb (205 kg)	17.6 ft ³ (.498 m ³)



BUCKETS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

HIGH VOLUME BUCKETS

Price Book	Description	Industry Part Number	Inside Dim.	Outside Dim.	Height	Depth	Weight	Heaped Capacity
FSA1040	BERLON HIGH VOLUME BUCKET – 60 in	HVMB-60	60 in (153 cm)	61.5 in (156 cm)	29 in (74 cm)	39 in (99 cm)	510 lb (230 kg)	27.5 ft ³ (.779 m ³)
FSA1045	BERLON HIGH VOLUME BUCKET – 66 in	HVMB-66	66 in (170 cm)	67.5 in (171 cm)	29 in (74 cm)	39 in (99 cm)	553 lb (251 kg)	30.2 ft ³ (.885 m ³)
FSA1050	BERLON HIGH VOLUME BUCKET – 72 in	HVMB-72	72 in (180 cm)	73.5 in (187 cm)	29 in (74 cm)	39 in (99 cm)	573 lb (260 kg)	33.1 ft ³ (.937 m ³)

BUCKETS – COMPACT ARTICULATED LOADERS

	ATX960
FSA1000	X
FSA1005	X
FSA1010	X
FSA1015	X
FSA1020	X
FSA1025	X
FSA1030	X
FSA1035	X
FSA1040	X
FSA1045	X
FSA1050	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



GRAPPLES

SPECIFICATIONS

GRAPPLES						
Price Book	Description	Industry Part Number	Weight	Claw Opening	Max Capacity	Hydraulic Cylinder
FSA1420	BERLON FOREST- RY CLAW – 60 in	BFC	261 lb (118 kg)	60 in (153 cm)	2,000 lb (900 kg)	2,500 psi (17 MPa)
FSA1425	BERLON LIGHTDUTY GRAPPLE – 54 in SINGLE CLAW	LDGR54	491 lb (223 kg)	41 in (100 cm)	2,000 lb (900 kg)	2,500 psi (17 MPa)
FSA1430	BERLON LIGHTDUTY GRAPPLE – 60 in SINGLE CLAW	LDGR-60	524 lb (238 kg)	41 in (100 cm)	2,000 lb (900 kg)	2,500 psi (17 MPa)
FSA1435	BERLON LIGHTDUTY GRAPPLE – 66 in SINGLE CLAW	LDGR-66	557 lb (253 kg)	41 in (100 cm)	2,000 lb (900 kg)	2,500 psi (17 MPa)
FSA1440	BERLON LIGHTDUTY GRAPPLE – 66 in DUAL CLAW	MDGR-66	735 lb (333 kg)	41 in (100 cm)	2,500 lb (1,100 kg)	2,500 psi (17 MPa)
FSA1445	BERLON LIGHTDUTY GRAPPLE – 72 in DUAL CLAW	MDGR-72	770 lb (350 kg)	41 in (100 cm)	2,500 lb (1,100 kg)	2,500 psi (17 MPa)
FSA1405	VERMEER FSLG54 – SWIVEL LOG GRAPPLE	NA	680 lb (310 kg)	54 in (140 cm)	2,700 lb (1,200 kg)	3,100 psi (21 MPa)
FSA1410	VERMEER FRLG54 – HYD ROTATING LOG GRAPPLE	NA	750 lb (340 kg)	54 in (140 cm)	2,700 lb (1,200 kg)	3,100 psi (21 MPa)



GRAPPLES

ATTACHMENT COMPATIBILITY

GRAPPLES – COMPACT ARTICULATED LOADERS

	ATX960
FSA1420	X
FSA1425	X
FSA1430	X
FSA1435	X
FSA1440	X
FSA1445	X
FSA1405	X
FSA1410	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



TRENCHERS

SPECIFICATIONS AND ATTACHMENT COMPATIBILITY

TRENCHERS							
Price Book	Description	Industry Part Number	Max Weight	Max Trench Depth	Max Trench Width	Max Flow	Max Pressures
FSA1455	VERMEER TRENCHER ATTACHMENT – FTR48	NA	700 lb (300 kg)	48 in (120 cm)	8 in (20 cm)	25 gpm (95 L/min)	3,100 psi (21 MPa)

TRENCHERS – ARTICULATED LOADERS	
	ATX960
FSA1455	X

■ COMPATIBLE
 ■ COMPATIBLE BUT NOT RECOMMENDED
 ■ NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



FORKS

SPECIFICATIONS

PALLET FORKS (RAIL STYLE)

Price Book	Description	Industry Part Number	Weight	Fork Length	Rated Capacity
FSA1500	BERLON CLASS II PALLET FORKS – RAIL STYLE 48 in	BPFF-48-2	415 lb (188 kg)	48 in (120 cm)	4,000 lb (2,000 kg)
FSA1505	BERLON CLASS II PALLET FORKS – RAIL STYLE 54 in	BPFF-54	434 lb (197 kg)	54 in (140 cm)	5,500 lb (2,500 kg)

SQUARE BALE SPEAR

Price Book	Description	Industry Part Number	Weight	Width	Height	Bottom Tines (quantity)
FSA1700	BERLON SQUARE BALE SPEAR – 52 in WIDE	BSC-3324	182 lb (82.6 kg)	52 in (130 cm)	39 in (99 cm)	3

MANURE FORKS

Price Book	Description	Industry Part Number	Weight	Width	Replaceable Tines (quantity)
FSA1710	BERLON MANURE FORK – 54 in WIDE	MTMF-54	329 lb (149 kg)	54 in (140 cm)	9
FSA1715	BERLON MANURE FORK – 60 in WIDE	MTMF-60	362 lb (164 kg)	60 in (153 cm)	10



FORKS

ATTACHMENT COMPATIBILITY

PALLET FORKS (RAIL STYLE) – COMPACT ARTICULATED LOADERS

	ATX960
FSA1500	X
FSA1505	X

SQUARE BALE SPEAR – COMPACT ARTICULATED LOADERS

FSA1700	X
---------	---

MANURE FORKS – COMPACT ARTICULATED LOADERS

FSA1710	X
FSA1715	X

 COMPATIBLE  COMPATIBLE BUT NOT RECOMMENDED  NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the Color Key at the beginning or end of this brochure for more information about attachment use and compatibility.



COLOR KEY

 **COMPATIBLE**  **COMPATIBLE BUT NOT RECOMMENDED**  **NOT AUTHORIZED**

COMPATIBLE: The attachment is compatible with the associated base unit. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

COMPATIBLE BUT NOT RECOMMENDED: The attachment is technically compatible but not recommended for combined use with the associated base unit. Functionality, reliability or performance may be limited; damage to or excess wear and tear on the attachment or base unit is possible. Note that use of attachments that are not recommended by Vermeer and that (in the sole judgment of Vermeer) amounts to abnormal use, misuse or negligence will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

NOT AUTHORIZED: The attachment is not authorized for use with the associated base unit. Combined use may be technically infeasible or pose unacceptable risk of harm to property or persons. Never operate these attachments and base units in combination. Note that use of these attachments, in addition to being unsafe, will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

Vermeer Corporation
1210 Vermeer Road East
Pella, Iowa 50219
800-370-3659

vermeer.com

Vermeer Corporation and MultiOne SRL Corporation reserve the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Mini skid steer attachments available from Vermeer dealers may be manufactured by Vermeer Corporation or other attachment manufacturers. Please contact your local Vermeer dealer for more information on machine specifications and attachments.

Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. All other trademarks, registered trademarks and service marks are the property of their respective owners.

© 2023 Vermeer Corporation. All Rights Reserved.



ATTACHMENTS