

ATX530

COMPACT ARTICULATED LOADER



TELESCOPIC BOOM. The telescopic boom on the ATX530 extends 21.6 in (54.9 cm) for loading materials to a dump height of 108.3 in (275.1 cm) in hinge pin height. The telescopic boom can also aid in dumping material over the back of a retaining wall or grabbing material over an obstruction.



COMPACT SIZE. With narrow tires, the ATX530 is 38.6 in (98 cm) wide, while the wider tires make the machine 42.9 in (109 cm) wide. Both configurations allow the ATX530 to fit through a standard 4-ft (1-m) gate for backyard access on landscape jobs. The overall length of the ATX530 is 98.4 in (250 cm).



LIFT-CAPACITY-TO-WEIGHT RATIO. The ATX530 has a rated operating capacity (straight) of 1,343 lb (609.2 kg)* while having a standard weight of 2760 lb (1252 kg) with rear weights and without attachments. This lift-capacity-to-weight ratio allows contractors to utilize a lighter machine while still being able to carry heavy materials on the jobsite.



MULTIFUNCTION JOYSTICK. The multifunction joystick utilizes electric-over-hydraulic toggles for ease of access to machine functions like the telescopic boom, auxiliary hydraulic controls and the DBS. The operator does not have to remove their hand from the loader arm controls in order to function any of these features.



FOUR-WHEEL DRIVE HYDROSTATIC DIRECT DRIVE MOTORS. As each wheel has a hydrostatic direct drive motor, hydraulic oil can flow freely to each wheel as needed during transport which helps reduce ground disturbance on turf when making turns. The four-wheel drive hydrostatic direct drive motors also allow for the use of the DBS and torque divider to increase tractive effort in difficult conditions.



OPERATOR COMFORT. The adjustable seat and operator station layout allows operators to work comfortably for a full day. Options like a heated seat, enclosed and heated cab, and work lights add comfort for year-round use of the ATX530.

ATX530 COMPACT ARTICULATED LOADER

GENERAL DIMENSIONS

Length (with rear weights): 98.4 in (250 cm)

Width (varies with tire size): 42.9 in (109 cm)

Height (with cab): 77.2 in (196 cm)

Weight (with rear weights and no attachments): 2,756 lb (1,250 kg)

Ground clearance: 7.9 in (20 cm)

Angle of departure with rear weights: 19° angle

ENGINE

Make/model: Kubota D1305 Tier 4 Final

Fuel type: Diesel

Fuel tank capacity: 6.3 gal (24 L)

Gross horsepower: 25 hp (19 kW)

Cooling system: Liquid

Transmission: Hydrostatic

PERFORMANCE

Rated operating capacity (straight)*: 1,343 lb (609.2 kg)

Rated operating capacity (articulated)*: 1,141 lb (517.5 kg)

Travel speed: 5.8 mph (9.3 km/hr)

Pushing force: 900 kp (900 kgf)

Turning radius (inside/outside): 31.5 in - 78.7 in
(80 cm - 200 cm)

Standard tires: 23x10.50-12 ET-25

Pivot point height (extended boom): 108.3 in (275 cm)

Outreach with horizontal boom (extended boom): 35.4 in (89.9 cm)

*Operating capacities shown have the boom low to the ground, boom not extended and the rear counterweights installed. The rating shown is for a fork attachment at 80% of the tipping load per EN 474-3:2006+A1:2019.

HYDRAULIC SYSTEM

Auxiliary hydraulics oil flow: 13.2 gpm (50 L/min)

Two pumps with HI-Flow System

Hydraulic oil tank capacity: 7.9 gal (30 L)

STANDARD FEATURES

Dynamic block system (DBS)

Seat with adjustable position

Four-wheel drive hydrostatic direct drive motors

Hydraulic multi-connector

Multifunction joystick

Self-leveling double-h telescopic boom

Two front-working lights

OPTIONS

Additional auxiliary hydraulics (front)

Additional auxiliary hydraulics (rear)

Beacon lights

Engine block heater

Floating boom valve

Fully enclosed cab

Heating system for cab

LED work lights

Plexiglass back window

Plexiglass right-side window

Plexiglass windscreen

Rear protection bar

Rear 12V electrical power

Tire and tread options

Torque divider

VERMEER STANDARD LIMITED WARRANTY

2 year/1,000 hour standard warranty

3 year/1,000 hour extended service coverage on all hydraulic pumps and wheel drive motors

MultiOne, SRL Corporation reserve the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are all trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kubota is a trademark of Kubota Engine Corporation.

© 2023 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

Vermeer



EQUIPPED TO
DO MORE.