ML100 MINI LOADER BUILT TO LEAD.

BUILT TO LIFT. **BUILT TO LAST.**

POWERFUL PRODUCTIVITY

Get ready for more power when the job demands it. Featuring a turbocharged 24.7-hp (18.4 kW) diesel engine and increased operating capacity, the ML100 is built for pros who demand more.

SMARTER, STRONGER OPERATION

Compared to previous models, the enhanced hydraulic system on the ML100 helps optimize filtration to minimize oil contamination, improving hydraulic component longevity and maximizing the efficiency of tractive effort. This provides operators with greater confidence to power through tough jobs.

OPERATOR-FOCUSED DESIGN

The Vermeer ML100 is built for long days and rough terrain. The cushioned chariot-style operator station is designed for protection and fatigue reduction - keeping you comfortable, secure and focused from first light to last load.

VERSATILE AND COMPATIBLE

When you have the right attachments, you can tackle more jobs in less time. Vermeer offers a comprehensive lineup of high-quality common industry interface (CII) attachments that are rigorously tested to ensure compatibility on the ML100 - providing the best possible ownership experience.

BUILT-IN CONFIDENCE

Bring peace of mind to every job site. Beyond the standard warranty, the ML100 comes equipped with additional coverage on the loader arms, mainframe and Rehlko engine. And with support from your local Vermeer dealer, service and expertise are always close by.

MAINTENANCE-FRIENDLY

Spend less time on maintenance and more time getting the work done. With toolless engine access panels, routine maintenance charts and a spring tensioned greaseless track system, upkeep is simple - allowing you to stay focused on the job.



LEARN MORE ABOUT THE ML100



ML100 MINI LOADER

GENERAL

Length: 84 in (213 cm)

Width with 7 in (17.8 cm) tracks: 36 in (91 cm) **Width with 9 in (22.9 cm) tracks:** 40 in (102 cm)

Height: 58 in (147 cm)

Hinge pin height: 84.5 in (215 cm)

Weight (wide tracks): 3,466 lb (1572 kg)



Make: Rehlko 1403 KSD-TC

Gross horsepower: 24.7 hp (18.4 kW)

Fuel type: Diesel

Fuel tank capacity: 13.0 gal (49.2 L)

PERFORMANCE

Rated operating capacity (SAE): 950 lb (431 kg)

Max travel speed: 4.2 mph (6.8 km/h)

HYDRAULICS

Auxiliary high flow: 12.1 gpm (45.8 L/min)

Auxiliary low flow: 5.2 gpm (19.7 L/min)

Hydraulic system pressure: 3,045 psi (210 bar)

| NOTES: | | | | |
|---------------|--|--|--|--|
| | | | | |
| | | | | |
| | | | | |
| | | | | |



FIND YOUR LOCAL VERMEER DEALER







Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Vermeer Confidence Plus and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries.

© 2025 Vermeer Corporation. All Rights Reserved.

10/25 PN 296431687