



DUAL HORIZONTAL OFFSET FEED ROLLERS. Improve performance by aggressively grabbing and feeding material to the drum. The offset helps the upper feed roller climb over big logs or material with lots of branches and forks.



EASILY LIFTS HEAVY MATERIAL. An optional winch allows operators to move large logs effortlessly. The 150 ft (45.7 m) winch line can handle logs up to 2000 lb (907.2 kg) and can be used to lift the log onto the feed table.



ELECTRONIC FUEL INJECTION ENGINE. With improved fuel economy, the 135 horsepower (101 kW) Power Solutions International (PSI) engine allows for more efficient working conditions and boosts engine response under load.



A CLUTCHLESS PTO SYSTEM. Avoids premature wear to the belt-drive system by preventing high-speed engagement of the cutter drum. The throttle is integrated with the belt drive to help ensure the PTO can be engaged only while the engine is at low speed.



EXTENDED WARRANTY. The 3-year/ 3000-hour extended limited warranty on drum housing, cutter drum, shaft and ring-fetter hubs offers you peace of mind, in addition to the 1-year/1000-hour Vermeer equipment limited warranty.



ECOIDLE™ ENGINE CONTROL SYSTEM.

When the Ecoldle™ function is selected by the operator, the engine speed automatically lowers to a preset rpm after 1 minute or 5 minutes of inactivity to help reduce fuel consumption when not chipping material. Due to this idling, noise and greenhouse emissions are also reduced.

Vermeer











BC1200XL GAS BRUSH CHIPPER

GENERAL

Length: 168" (426.7 cm) Width: 79" (200.7 cm) Height: 103" (261.6 cm)

Weight (with winch): 5980 lb (2712.49 kg)

Weight: 5680 lb (2576.4 kg)

ENGINE

Make/Model: PSI 4.XL Electronic Fuel Injection

Horsepower: 135 hp (101 kW)

Max torque: 258 ft-lb (349.8 Nm) @1400 rpm

Fuel type: Gasoline Number of cylinders: 6 Cooling medium: Liquid

FEED SYSTEM

Chipping capacity (max): 13.3" (33.8 cm) Infeed opening height: 32" (81.3 cm) Infeed opening width: 52" (132.1 cm) Feed roller orientation: Dual horizontal offset

Feed table height: 32" (81.3 cm) Feed speed (max): 110 fpm

Feed roller dimensions (upper roller): 15" (38.1 cm) diameter x

17" (43.2 cm)

Feed roller dimensions (lower roller): 11.1" (28.2 cm) diameter x

17" (43.2 cm)

CUTTING SYSTEM

Drum dimensions: 20" diameter x 20" wide (50.8 cm x 50.8 cm)

Drum speed: 2000 rpm Knives: Two A8 chipper steel Bedknife: Four usable edges

CAPACITIES/ELECTRICAL

Fuel tank: 25 gal (94.6 L) Hydraulic tank: 12 gal (45.4 L)

System voltage: 12 V

Lights: LED brake, turn, tail, license, side indicators

CHASSIS/BRAKES

Frame: 7" x .25" (17.8 cm x .6 cm) Z-channel Tires (option 1): ST235/80/R16 Load Range E Tires (option 2): ST285/75/R16 Load Range E

Axle/Suspension: 7000 lb (3175.2 kg) rubber torsion

Electrical brakes with breakaway switch

OPTIONS

Extended warranty

Special paint

Planned maintenance

Vermeer Confidence Plus® asset protection program

NOTES:

Vermeer

EQUIPPED TO **DO MORE**

logo, Ecoldle, Equipped to Do More and Vermeer Confidence Plus are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. PSI is a trademark of Power Solutions International Inc