

# FT300 FORESTRY TRACTOR



**ROBUST HYDRAULIC SYSTEM.** The hydraulic system is designed to operate below its rated capacity for extended life of hydraulic components compared to competitive units.



**SELF-POSITIONING DEFLECTOR.** The patent-pending self-positioning thrown object deflector helps direct thrown material at a consistent discharge angle, regardless of head position.



**EASY ON THE OPERATOR.** With a spacious cab, featuring air-ride seating, user-friendly controls and optimal viewing area supported with a standard rearview camera, operators can focus on production.



**SERVICEABILITY.** A center-mounted cooling package is easy to access, and two large hinged doors swing open to expose the engine compartment for maintenance without additional tools.



**ROTOR PERFORMANCE.** The externally balanced, ringed rotor helps guide material to the cutting tips for a more clean cutting path while also controlling the depth of cut. Interchangeable tip options allow operators to customize cutting performance to meet their jobsite needs.



**TRACK OPTIONS.** With the option of either steel or low ground pressure (LGP) tracks, operators can choose which style fits their jobsite needs. With the weight of the mulcher head calculated in, the total machine weight is centered on the tracks resulting in even weight distribution and lower ground pressure.

# FT300 FORESTRY TRACTOR

## GENERAL DIMENSIONS AND WEIGHTS

Tractor length: 22.3' (6.8 m)

Tractor width: 98" (248.9 cm)

Tractor height: 116.7" (296.4 cm)

Tractor weight – track option one: 26,460 lb (12,002.1 kg)

Tractor weight – track option two: 33,100 lb (15,013.9 kg)

Tractor weight range with above-ground mulcher: 32,460 to 39,100 lb (14,723.6 to 17,735.5 kg)

Ground clearance: 14.5" (36.8 cm)

## ENGINE OPTION ONE

Make/Model: Cummins QSL9 Tier 4 Final

Rated horsepower: 300 hp (223 kW)

Rated engine rpm: 2200

Number of cylinders: 6

Fan-type: Reversible

Fuel tank capacity: 137 gal (518.6 L)

DEF fluid capacity: 10 gal (37.9 L)

## ENGINE OPTION TWO

Make/Model: Cummins QSC290 Tier 3

Rated horsepower: 290 hp (216 kW)

Rated engine rpm: 2200

Number of cylinders: 6

Fan-type: Reversible

Fuel tank capacity: 137 gal (518.6 L)

Contact your local Vermeer dealer for engine availability in your region.

## TRACK OPTION ONE

Make/Model: Track Industries – low ground pressure (LGP)

Track pad type: 5-ply strips with cross bars

Track pad width: 33.25" (84.5 cm)

Ground pressure – tractor only: 3.2 psi (22.1 kPa)

Ground pressure – with above-ground mulcher: 3.9 psi (26.9 kPa)

Max ground speed – low: 3 mph (4.8 km/h)

Max ground speed – high: 6 mph (9.7 km/h)

## TRACK OPTION TWO

Make/Model: Berco – D4

Track pad type: Single grouser

Track pad width: 30" (76.2 cm)

Ground pressure – tractor only: 4.3 psi (29.6 kPa)

Ground pressure – with above-ground mulcher: 5 psi (34.5 kPa)

Max ground speed – low: 3 mph (4.8 km/h)

Max ground speed – high: 6 mph (9.7 km/h)

## CAB

Egress points: 3 – left and right door, roof hatch

Control system: Dual joystick

Air suspension seat: Standard

Display: 7" (17.8 cm) color

Rear-camera: Color, infrared, standard

Number of work lights: 11

Work light-type: LED

## HYDRAULIC SYSTEM

Oil tank capacity: 57 gal (215.8 L)

Attachment pressure limiter setting: 4000 psi (275.8 bar)

Attachment pump flow at max rpm: 145 gpm (548.9 L/min)

## ABOVE-GROUND MULCHER

Overall attachment width: 100" (254 cm)

Attachment weight: 6000 lb (2721.6 kg)

Working width: 82.5" (209.6 cm)

Quantity of cutting teeth: 23

Tip option one: Sharp planar

Tip option two: Clad-faced planar

Tip option three: Impact-resistant hammer

## OPTIONS

Electric-actuated engine air shutoff

Arctic package (diesel-fired fluid heater)

Rear-mounted winch: 30,000 lb (13,607.8 kg)

Vermeer Confidence Plus® asset protection program

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More and Vermeer Confidence Plus are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Cummins is a trademark of Cummins Inc. Berco is a trademark of Berco S.p.A. Track is a trademark of Track Industries, Ltd. © 2016 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

