ML150 MINI LOADER

MORE LIFT. MORE POWER. MORE MACHINE.

MAXIMIZED PRODUCTIVITY

Get ready for powerful performance and maximum lift capacity. Featuring a 40-hp (29.8 kW) turbocharged diesel engine for big jobs and demanding attachments, the ML150 is ready for whatever the job calls for.

SMARTER, STRONGER OPERATION

Compared to previous models, the enhanced hydraulic system on the ML150 helps optimize filtration to minimize oil contamination, improving hydraulic component longevity and maximizing the efficiency of tractive effort. This provides operators with greater confidence to power through tough jobs.

OPERATOR-FOCUSED DESIGN

The Vermeer ML150 is built for long days and rough terrain. The cushioned chariot-style operator station is designed for protection and fatigue reduction - keeping you comfortable, secure and focused from first light to last load.

comes equipped with additional coverage

on the loader arms, mainframe and Rehlko

engine. And with support from your local

Vermeer dealer, service and expertise are

always close by.

BUILT-IN CONFIDENCE Bring peace of mind to every job site. Beyond the standard warranty, the ML150

When you have the right attachments, you can tackle more jobs in less time. Vermeer offers a comprehensive lineup of high-quality common industry interface (CII) attachments that are rigorously tested to ensure compatibility on the ML150 - providing the best possible ownership experience.

VERSATILE AND COMPATIBLE

Spend less time on maintenance and more

MAINTENANCE-FRIENDLY

time getting the work done. With toolless engine access panels, routine maintenance charts and a spring tensioned greaseless track system, upkeep is simple - allowing you to stay focused on the job.



LEARN MORE ABOUT THE ML150



ML150 MINI LOADER

GENERAL

Length: 92.5 in (235 cm) **Width:** 42 in (107 cm)

Height: 59 in (150 cm)

Hinge pin height: 88 in (224 cm)

Weight: 4,000 lb (1814 kg)



Make: Rehlko 1903 KDI-TCR

Gross horsepower: 40 hp (29.8 kW)

Fuel type: Diesel

Fuel tank capacity: 13.0 gal (49.2 L)

PERFORMANCE

Rated operating capacity (SAE): 1,530 lb (694 kg)

Max travel speed: 4.4 mph (7.1 km/h)

HYDRAULICS

Auxiliary high flow: 16.8 gpm (63.6 L/min) **Auxiliary low flow:** 9.4 gpm (35.6 L/min)

Hydraulic system pressure: 3,045 psi (210 bar)

NOTES:			







FIND YOUR LOCAL VERMEER DEALER



Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Vermeer Confidence Plus, and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries.

© 2025 Vermeer Corporation. All Rights Reserved.

10/25 PN 296431689