

# CTX160 MINI SKID STEER



**OPTIMAL POWER.** Equipped with a 40-hp (29.8-kW) turbocharged Kohler KDI diesel engine. This engine eliminates the need for a diesel particulate filter (DPF), helping reduce cost and complexity of the engine.



**HIGH-CAPACITY LIFTING.** The vertical lift capability on the CTX160 boasts a rated (SAE) operating capacity of 1600 lb (725.7 kg) and a hinge pin height of 88.75 in (225.4 cm).



**DUAL HYDRAULIC SYSTEM.** The CTX160 dual hydraulic system is capable of providing 16.7 gpm (63.2 L/min) of hydraulic flow, powering demanding attachments. Low flow offers 9.4 gpm (35.6 L/min) to give maximum control.



**OPERATOR STABILITY.** Designed with comfort in mind, the chariot-style operator's station is paired with operator presence on the CTX160, giving the operator confidence while working on demanding jobs.



**COMPACT FOOTPRINT.** This unit is designed to get through standard residential gates and into tight access areas. With 9-in (22.9 cm) tracks, the CTX160 is 42 in (106.7 cm) in total width. Offering maximized traction and low ground pressure.



**LOADER ARM WARRANTY.** The CTX160 comes with a 3-year/3,000-hour limited warranty on the loader arms.

# CTX160 MINI SKID STEER

## GENERAL

Length with standard bucket: 116 in (294.6 cm)

Length without standard bucket: 92.5 in (234.95 cm)

Width with standard bucket 9 in (22.9 cm) tracks: 42 in (106.7 cm)

Height: 59 in (149.9 cm)

Height (to hinge pin): 88.75 in (225.4 cm)

Ground clearance: 6.75 in (17.1 cm)

Weight [standard bucket, diesel engine, 9 in (22.9 cm) tracks]: 4115 lb (1866.5 kg)

Weight [no bucket, diesel engine, 9 in (22.9 cm) tracks]: 4000 lb (1814.4 kg)

## ENGINE

Make/Model: Kohler KDI 1903

Fuel type: Diesel

Fuel tank capacity: 14.5 gal (54.9 L)

Gross horsepower: 40 hp (29.8 kW)

Cooling system: Liquid

Max angle of inclination (intermittent): 30°

## TRACK PERFORMANCE

Rated operating capacity (SAE): 1600 lb (725.7 kg)

Travel speed (forward): 4.4 mph (7.1km/h)

## OPERATIONAL

Steering: Dual-axis, pilot-operated joystick

Lift: Dual-axis, common bucket lever

Curl: Dual-axis, common bucket lever

## HYDRAULIC SYSTEM

Hydraulic auxiliary system high flow: 16.7 gpm (63.2 L/min)

Hydraulic system low flow: 9.4 gpm (35.6 L/min)

Hydraulic system pressure: 3045 psi (209.9 bar)

Ground pressure: 4.7 psi (.32 bar)

Hydraulic tank capacity: 12 gal (45.4 L)

**NOTES:**

---

---

---

---

---

---

---

---

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Mini skid steer attachments available from Vermeer dealers may be manufactured by Vermeer Corporation or other attachment manufacturers. Please contact your local Vermeer dealer for more information on machine specifications and attachments. Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a trademark of Kohler Co. © 2020 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

