

VXT600 VACUUM TRUCK



WEIGHT. Elongated spoil tank design with even weight distribution makes it the lightest vacuum truck in its size class. The spoil tank has a full-open cam-over rear door and lifts to a 50-degree angle for quick offloading.



ULTRA QUIET. Jurop 6,400-cfm (181.2-m³/min) blower capable of 27 inHg (.91 bar) while keeping noise at a minimal.



SIDE STOW BOOM. Side stow boom allows for quick jobsite setup by allowing the dig tube to always stay connected.



SPOIL TANK VIBRATOR. Optional vibrator allows for a more efficient way of dumping.



AIR COMPRESSOR. Optional 180-cfm (5-m³/min), 110-psi (7.58-bar) compressor option for air excavation and pneumatic tools.



AVAILABLE WINTER OPTIONS. Optional water heater and winter packages for operation in cold climates.

VXT600 VACUUM TRUCK

GENERAL DIMENSIONS	VXT600 WITH TRUCK
Length	33.4 ft (10 m)
Width	98 in (249 cm)
Height with boom	12.25 ft (4 m)
Empty weight	40,000 lb (18,144 kg)
TRUCK SPECS	
Truck model	Kenworth T880
Engine	510 hp (380 kW)
Engine model	MX-13
Transmission	ALLISON 4500
GVWR	86,000 lb (39,009 kg)
TRUCK SPECS	
Truck model	Mack Granite
Engine	505 hp (377 kW)
Engine model	MP8
Transmission	ALLISON 4500
GVWR	86,000 lb (39,009 kg)
WATER TANK	
Water tank capacity	1,200 gal (4,542 L)
Water pump	10 gpm (37.9 L/min) at 3,000 psi (206.8 bar), optional 19.4 gpm (73.4 L/min)
High pressure hose length	75 ft (23 m)
SPOIL TANK	
Spoil tank capacity	12 yd ³ (11 m ³)
Door type	Cam-over hydraulic
In-tank washdown	Standard
Mechanical full-tank shutoff	Standard
Tank lift type	Telescopic cylinder
VACUUM	
Type of filters	2-micron washable filter
Dig tools	5 ft (1.5 m) dig tool 8 in (20 cm) diameter, 5 ft (1.5 m) dig tool 6 in (15 cm) diameter, (3) 5 ft (1.5 m) extensions 8 in (20 cm) diameter
Dig tool diameter	8 in (3.14 cm)
Boom length	23 ft (7 m)
Vacuum max flow	6,400 cfm (181.2 m ³ /min)
Vacuum max suction	27 inHg (.91 bar)
Vacuum blower model	JUROP
CONTROLS	
Display	Electronic display with 7-in (17.8-cm) LCD screen
Remote	Full-function wireless remote (optional belly pack or handheld)
OPTIONS	
Dynablast 420FLS hot water heater	420,000 BTU
Cold weather option	Heated cabinets, water lines and valves
Vibrator	Spoil tank mounted vibrator
Onboard air compressor	180 cfm (5 m ³ /min), 110 psi (7.58 bar)
Water pump	19.4 gpm (73.4 L/min)

Vermeer MV Solutions, Inc. reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. All other trademarks, registered trademarks and service marks are the property of their respective owner. © 2023 Vermeer MV Solutions, Inc. All Rights Reserved. Printed in the U.S.A. Please recycle.

