



WHEN THERE'S A JOB TO BE DONE. With 28,000 lb (124.6 kN) of thrust/pullback and 4,200 ft-lb (5694.4 Nm) of rotational torque, the D24x40 S3 offers an increase over its predecessor, helping to maximize machine and jobsite productivity.



TOP OF ITS CLASS. With a class-leading carriage speed of 240 fpm (73.2 m/min) - more than 20% faster than its closest competitor - the D24x40 S3 helps contractors install more linear feet per day.



INSTALL PRODUCT FASTER. The D24x40 S3 features a 270 rpm rotational speed that rivals larger drills and outpaces competitive models by 18% - helping contractors complete jobs faster.



SIGNIFICANT SOUND REDUCTION. With a 104 dB(A) guaranteed sound power level and an operator ear rating of 82.9 dB(A), as well as an in-cab operator ear rating of 75.7 dB(A), the D24x40 S3 contributes to a quieter working environment, creating less neighborhood disturbance and enabling easier communication among the crew.



COMFORTABLE CAB. The excavator-style cab offers operators more legroom and greater comfort.



AURORA™ TOUCHSCREEN DISPLAY. Interactive full-color touchscreen display delivers real-time, easy-to-view locate information, bore plans and more that can help increase productivity.











D24x40 S3 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

GENERAL WEIGHTS AND DIMENSIONS

Min transport length: 20.1 ft (6.1 m)

Min transport width: 89 in (226.1 cm)

Min transport height: 76 in (193 cm)

Height (with cab): 102 in (259.1 cm)

Min weight: 20,700 lb (9,389.3 kg)

Max weight: 22,250 lb (10,092.4 kg)

ENGINE OPTION ONE

Make and model: John Deere Series 4045

Fuel type: Ultra low sulfur diesel

Max engine rpm: 2400 rpm

Gross horsepower: 125 hp (93 kW)

Displacement: 275 cu in (4.5 L)

Cooling method: Liquid

Emissions rating: Tier 4 Final (EU Stage V)

ENGINE OPTION TWO

Make and model: John Deere Series 4045

Fuel type: Diesel

Aspiration: Turbo

Max engine rpm: 2,400 rpm

Gross horsepower: 125 hp (93 kW) Displacement: 275 cu in (4.5 L)

Cooling method: Liquid

Aspiration: Turbo

Emissions rating: Tier 3 (EU Stage IIIA)

OPERATIONAL

Thrust/Pullback: 28,000 lb (124.6 kN)

Max carriage speed at max engine rpm: 240 fpm (73.2 m/min)

Max spindle torque (low at max engine rpm): 4,200 ft-lb (5,694.4 Nm)

Max spindle speed at max engine rpm: 270 rpm

Min bore diameter: 4 in (10.2 cm)

Max ground drive speed at max engine rpm (fwd): 3.3 mph (5.3 km/h)

Noise level at operator's ear: 82.9 dB(A)

Noise level at operator's ear (cab): 75.7 dB(A)

Drill rack angle: 14-21° (24.9-38.4%)

FLUID CAPACITIES

Fuel tank: 44 gal (166.6 L)

Antifreeze tank capacity: 3.9 gal (14.7 L)

DRILLING FLUID SYSTEM

Max flow: 50 gpm (189.3 L/min) **Max pressure:** 1,050 psi (7.2 MPa)

FEATURES

Breakout system: Standard hydraulic vise

Drilling lights: Standard
Flow indicator: Standard
Stakedown system: Standard

Cab: Optional

Strike alert: Standard
Remote lockout: Standard

DRILL PIPE

Type: Firestick® drill rod

Length: 10 ft (3 m)

Rod diameter: 2.38 in (6 cm) Weight: 73 lb (33.1 kg) Bend radius: 108.2 ft (33 m)

J	n	т	FS	
ч	v			•

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Aurora is a registered trademark of Digital Control Incorporated. John Deere is a registered trademark of Deere & Company. © 2023 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

