

# XTS1250i2 RIDE-ON TRACTOR



**STEEL QUAD TRACK SYSTEM.** Four independent steel tracks can offer enhanced floatation and traction with four-wheel and crab steering options.



**OPTIMIZED PRODUCTIVITY.** The XTS1250i2 offers a productivity advantage with classic and newly added intelligent features such as Ecolde™ engine control system and Productivity Zone.



**OPTIONAL REMOTE CONTROL.** Utilize an optional remote control for convenient maintenance and trailer loading and unloading.



**TELEMATICS READY.** Stay in-sync with, and get optimal productivity out of, your machine by adding telematics to this tractor.



**ENHANCED COMFORT.** The XTS1250i2 boasts a quiet ride, convenient controls and an isolated, cushioned operator's platform. An optional, all-new climate-controlled cab is also available.



**POWER FOR THE JOB.** The XTS1250i2 is powered by a 127 hp (95 kW) Deutz TCD3.6L diesel engine which offers efficient power for working in difficult ground conditions.



VERMEER.COM



EQUIPPED TO  
DO MORE.™

# XTS1250i2 RIDE-ON TRACTOR

## GENERAL DIMENSIONS AND WEIGHTS

Length (basic tractor, steel tracks): 12.6' (3.8 m)

Width (steel tracks): 100.5" (255.3 cm)

Height (transport, 3-post): 10.2' (3.1 m)

Height (transport, cab): 10.2' (3.1 m)

Weight - tractor w/ open cab: 20215 lbs (9169 kg)

Weight - tractor w/ closed cab: 21265 lbs (9646 kg)

Roll over protection structure (open cab): 40000 lbs (18143.7 kg)

Roll over protection structure (enclosed cab): 40000 lbs  
(18143.7 kg)

## ENGINE OPTION ONE

Make and model: Deutz TCD3.6L

Fuel type: Ultra Low Sulfur Diesel

Maximum engine RPM: 2300

Idle speed: 1000

Gross horsepower: 127 hp (94.7 kw)

Torque (maximum): 369 lb/ft (500.3 Nm)

Number of cylinders: 4

Cooling method: Liquid

EPA certification family: Tier 4 (Stage IV)

Guaranteed sound power engine option 1: 104 dBa

## GROUND DRIVE - STEEL TRACKS

Ground pressure (basic tractor only, tracks): 14.7 psi (1.0 bar)

Maximum transport speed (fwd/rev): 7.1 mph (11.4 kmh)

Maximum creep speed (fwd/rev): 3.9 mph (6.3 kmh)

Maximum creep speed (fwd/rev): 342 fpm (104.2 mpm)

## FLUID CAPACITIES

Fuel tank: 44 gal (166.6 L)

Hydraulic tank: 31.6 gal (119.6 L)

## CAB FEATURES - (OPTIONAL)

Power port: 12-volt (2)

LED lights: Interior - LED, Exterior - LED

Radio standard: 2 speakers

## FEATURES

Service brake type: Hydrostatic

Parking brake type: Spring applied hydraulic release

Quad tracks: Four independent steel tracks bolt on to existing axle hubs

Telematics ready

Remote: optional

## NOTES:

---

---

---

Vermeer Corporation reserves the right to make changes in product engineering, design and specifications; add improvements; or discontinue manufacturing or distribution at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional or global-region specific features, accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More and Ecolidle are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Deutz is a trademark of Klockner-Humboldt-Deutz Corporation. © 2019 Vermeer Corporation. All Rights Reserved.

