

ATX720

COMPACT ARTICULATED LOADER



TELESCOPIC BOOM. The telescopic boom on the ATX720 extends 29.1 in (73.9 cm) for loading materials to a dump height of 114 in (289.6 cm) in hinge pin height. The telescopic boom can also aid in dumping material over the back of a retaining wall or grabbing material over an obstruction.



FRONT-SEATED ARTICULATION. Front-seated articulation helps the machine work in compact jobsites while keeping turf disturbance a priority.



LIFT-CAPACITY-TO-WEIGHT RATIO. The ATX720 has a rated operating capacity of 2,155 lb (978 kg) while having a standard weight of 3,549 lb (1,610 kg). This lift-capacity-to-weight ratio allows contractors to use a light machine while still being able to carry heavy materials on the jobsite.



COMPACT SIZE. With narrow tires, the ATX720 is 44.5-in (113-cm) wide, while the wider tires make the machine 50.4-in (128-cm) wide. The standard tire configuration allows the ATX720 to fit through a standard 4-ft (1.21-m) gate for backyard access on landscape jobs.



FOUR-WHEEL DRIVE HYDROSTATIC DIRECT DRIVE MOTORS. As each wheel has a hydrostatic direct drive motor, hydraulic oil can flow freely to each wheel as needed during transport which helps reduce ground disturbance on turf when making turns. The four-wheel drive hydrostatic direct drive motors also allow for the use of the DBS and torque divider to increase tractive effort in difficult conditions.



OPERATOR COMFORT. The adjustable seat and operator station layout allows operators to work comfortably for a full day. Options like a heated seat, enclosed and heated cab, and work lights add more comfort for year-round use of the ATX720.

