

ATTACHMENTS



MINI LOADER AND COMPACT ARTICULATED LOADER

REV. 5.1

CONTENTS

Universal mini attachments1

Buckets2

Augers8

Soil mowers11

Grapples.....15

Dozer blades21

Trenchers23

Plows25

Forks26

Cutters28

Snow tools30

Breakers.....32

Miscellaneous products34

Full-size attachments.....38

Buckets39

Grapples.....41

Trenchers.....43

Forks44



UNIVERSAL MINI ATTACHMENTS

 COMPATIBLE

 COMPATIBLE BUT NOT RECOMMENDED

 NOT AUTHORIZED

COMPATIBLE: The attachment is compatible with the associated base unit. Consult your operator’s manual or Vermeer dealer for additional information about attachment compatibility.

COMPATIBLE BUT NOT RECOMMENDED: The attachment is technically compatible but not recommended for combined use with the associated base unit. Functionality, reliability or performance may be limited; damage to or excess wear and tear on the attachment or base unit is possible. Note that use of attachments that are not recommended by Vermeer and that (in the sole judgment of Vermeer) amounts to abnormal use, misuse or negligence will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator’s manual or Vermeer dealer for additional information about attachment compatibility.

NOT AUTHORIZED: The attachment is not authorized for use with the associated base unit. Combined use may be technically infeasible or pose unacceptable risk of harm to property or persons. Never operate these attachments and base units in combination. Note that use of these attachments, in addition to being unsafe, will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator’s manual or Vermeer dealer for additional information about attachment compatibility.



Buckets help crews haul mulch, soil, gravel, debris and other loose material with less reliance on shovels and wheelbarrows. From loading to cleanup and placement, the right bucket can make common jobsite tasks easier to manage.

LOW PROFILE BUCKETS

MODEL	Berlon HD Low Profile Bucket – 36 in	Berlon HD Low Profile Bucket – 42 in	Berlon HD Low Profile Bucket – 48 in	Berlon HD Low Profile Bucket – 54 in
Model Number	UMA1000	UMA1005	UMA1010	UMA1015
Industry Part Number	MIB-36	MIB-42	MIB-48	MIB-54
Inside Dimension	36 in (91 cm)	42 in (107 cm)	48 in (122 cm)	54 in (140 cm)
Outside Dimension	37.5 in (95.3 cm)	43.5 in (110 cm)	49.5 in (126 cm)	55.5 in (141 cm)
Height	20 in (50 cm)	20 in (50 cm)	20 in (50 cm)	20 in (50 cm)
Depth	27 in (69 cm)	27 in (69 cm)	27 in (69 cm)	27 in (69 cm)
Weight	175 lb (79.4 kg)	195 lb (88.5 kg)	215 lb (97.5 kg)	235 lb (107 kg)
Heaped Capacity	7.5 ft ³ (.212 m ³)	8.8 ft ³ (.249 m ³)	10 ft ³ (.283 m ³)	11.3 ft ³ (.320 m ³)

TOOTH BUCKETS

MODEL	Berlon HD Tooth Bucket – 36 in	Berlon HD Tooth Bucket – 42 in	Berlon HD Tooth Bucket – 48 in	Berlon HD Tooth Bucket – 54 in
Model Number	UMA1020	UMA1025	UMA1030	UMA1035
Industry Part Number	MIB-36WET2	MIB-42WET2	MIB-48WET2	MIB-54WET2
Inside Dimension	36 in (91 cm)	42 in (107 cm)	48 in (122 cm)	54 in (137 cm)
Outside Dimension	37.5 in (95.3 cm)	43.5 in (110 cm)	49.5 in (126 cm)	55.5 in (141 cm)
Height	20 in (50 cm)	20 in (50 cm)	20 in (50 cm)	20 in (50 cm)
Depth	27 in (69 cm)	27 in (69 cm)	27 in (69 cm)	27 in (69 cm)
Weight	187 lb (84.8 kg)	207 lb (93.9 kg)	227 lb (103 kg)	257 lb (117 kg)
Heaped Capacity	7.5 ft ³ (.212 m ³)	8.8 ft ³ (.249 m ³)	10 ft ³ (.283 m ³)	11.3 ft ³ (.320 m ³)



MULCH BUCKETS

MODEL	Bradco Mulch Bucket – 34.5 in	Berlon Mulch Bucket – 48 in	Berlon Mulch Bucket – 54 in	Berlon Mulch Bucket – 60 in
Model Number	UMA1080	UMA1040	UMA1045	UMA1050
Industry Part Number	121153	MISLMB-48	MISLMB-54	MISLMB-60
Inside Dimension	NA	48 in (122 cm)	54 in (137 cm)	60 in (153 cm)
Outside Dimension	34.5 in (87.6 cm)	49 in (126 cm)	55.5 in (141 cm)	61.5 in (156 cm)
Height	NA	29 in (74 cm)	29 in (74 cm)	29 in (74 cm)
Depth	NA	39 in (99 cm)	39 in (99 cm)	39 in (99 cm)
Weight	239 lb (108 kg)	440 lb (200 kg)	465 lb (211 kg)	490 lb (220 kg)
Heaped Capacity	6 ft ³ (.170 m ³)	22 ft ³ (.623 m ³)	24.75 ft ³ (.701 m ³)	27.5 ft ³ (.779 m ³)

MISCELLANEOUS BUCKETS

MODEL	Vermeer High Dump Bucket – 48 in	Bradco 4-In-1 Bucket – 38 in	Bradco 4-In-1 Bucket – 42 in	Bradco Rock Bucket – 42 in	Bradco Power Shovel
Model Number	UMA1071	UMA1074	UMA1075	UMA1085	UMA1087
Industry Part Number	NA	18076-X	17767-X	19695-X	2000867-X
Inside Dimension	NA	NA	NA	NA	NA
Outside Dimension	48 in (122 cm)	38 in (97 cm)	42 in (107 cm)	42 in (107 cm)	25 in (64 cm)
Height	27.5 in (69.9 cm)	25 in (64 cm)	25 in (64 cm)	15 in (38 cm)	25 in (64 cm)
Depth	39 in (99 cm)	28 in (71 cm)	28 in (71 cm)	25 in (64 cm)	47 in (120 cm)
Weight	530 lb (240 kg)	250 lb (110 kg)	265 lb (120 kg)	180 lb (82 kg)	163 lb (73.9 kg)
Heaped Capacity	11.6 ft ³ (.328 m ³)	4.5 ft ³ (.127 m ³)	5 ft ³ (.142 m ³)	NA	NA





LOW PROFILE BUCKET

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1000	✓	✓	✓	✓	●	✓	✓	✓	✓
UMA1005	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1010	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1015	●	●	●	✓	✓	●	●	✓	✓

TOOTH BUCKET

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1020	✓	✓	✓	✓	●	✓	✓	●	●
UMA1025	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1030	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1035	X	●	●	✓	✓	●	●	✓	✓

MULCH BUCKET

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1080	✓	✓	✓	X	X	✓	✓	X	X
UMA1040	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1045	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1050	X	X	●	✓	✓	●	●	✓	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



MISCELLANEOUS BUCKETS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1071	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1074	✓	✓	✓	X	X	✓	✓	X	X
UMA1075	✓	✓	✓	X	X	✓	✓	X	X
UMA1085	✓	✓	✓	X	X	✓	✓	X	X
UMA1087	●	●	✓	✓	✓	✓	✓	✓	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



LOW PROFILE BUCKET

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1000	●	●	●	X
UMA1005	✓	✓	✓	X
UMA1010	✓	✓	✓	X
UMA1015	✓	✓	✓	X

TOOTH BUCKET

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1020	●	●	●	X
UMA1025	✓	✓	●	X
UMA1030	✓	✓	✓	X
UMA1035	✓	✓	✓	X

MULCH BUCKET

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1080	✓	✓	X	X
UMA1040	✓	✓	✓	X
UMA1045	✓	✓	✓	X
UMA1050	●	✓	✓	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.

MISCELLANEOUS BUCKETS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1071	✓	✓	✓	X
UMA1074	✓	✓	X	X
UMA1075	✓	✓	X	X
UMA1085	✓	✓	X	X
UMA1087	✓	✓	✓	X



✓ COMPATIBLE
● COMPATIBLE BUT NOT RECOMMENDED
X NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



Augers bore holes into the ground to handle much of the digging for fence posts, tree planting, sign installation, footing prep and other common landscape applications. They reduce the amount of manual labor needed for these jobs.

AUGER ATTACHMENTS

MODEL	Vermeer Auger Driver – 2 in Hex Pin Mount
Model Number	UMA1102
Weight	260 lb (120 kg)
Max Torque	2,509 ft-lb (3,402 Nm)
Max Pressure	3,100 psi (21 MPa)
Max Flow	20 gpm (76 L/min)

AUGER EXTENSIONS

MODEL	Berlon Extension – 14 in	Berlon Adapter – 2 in Hex to 2-9/16 in
Model Number	UMA1161	UMA1162
Industry Part Number	2HEX 3914E	H2-RD
Weight	35 lb (16 kg)	5 lb (2 kg)
Length	14 in (36 cm)	6 in (15 cm)

AUGER BITS

MODEL	Berlon Auger Bit – 6 in	Berlon Auger Bit – 9 in	Berlon Auger Bit – 12 in	Berlon Auger Bit – 15 in	Berlon Auger Bit – 18 in	Berlon Auger Bit – 24 in	Berlon Auger Bit – 30 in	Berlon Auger Bit – 36 in
Model Number	UMA1111	UMA1114	UMA1121	UMA1126	UMA1131	UMA1136	UMA1141	UMA1146
Industry Part Number	2HEX SQ-6H	2HEX SQ-9H	2HEX SQ-12H	2HEX SQ-15H	2HEX SQ-18H	2HEX SQ-24H	2HEX SQ-30H	2HEX SQ-36H
Weight	56 lb (25 kg)	83 lb (38 kg)	110 lb (50 kg)	145 lb (66 kg)	163 lb (74 kg)	203 lb (92 kg)	260 lb (120 kg)	340 lb (150 kg)
Width	6 in (15 cm)	9 in (23 cm)	12 in (30 cm)	15 in (38 cm)	18 in (46 cm)	24 in (61 cm)	30 in (76 cm)	36 in (91 cm)
Length	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)



AUGERS

specifications

ROCK AND TREE BITS

MODEL	Berlon Auger Bit – 9 in Rock	Berlon Tree Bit – 30 in	Berlon Tree Bit – 36 in
Model Number	UMA1117	UMA1151	UMA1156
Industry Part Number	2HEX RSQ-9H	2HEX SQ-T30H	2HEX SQ-T36H
Weight	90 lb (40 kg)	270 lb (120 kg)	350 lb (159 kg)
Width	9 in (23 cm)	30 in (76 cm)	36 in (91 cm)
Length	48 in (122 cm)	48 in (122 cm)	48 in (122 cm)





MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1102	✓	✓	✓	✓	✓	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1102	✓	●	✗	✗



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



SOIL MOWERS

specifications

Before seed, sod or landscaping goes down, crews need to get the ground ready. **Soil mowers**, or power rakes, break up packed soil, rake out rocks and debris, and level rough spots so the surface is ready for the next step.



SOIL MOWERS

MODEL	Tiller – 40 in x 4.5 in	Rotadairon Soil Renovator	Rotadairon Soil Renovator	Rotadairon Brush Mower / Mulcher
Model Number	MSSA305	UMA1331	UMA1333	UMA1336
Industry Part Number	B17766	STH-36	STH-42	BRD50
Width	40 in (100 cm)	38 in (97 cm)	43.3 in (110 cm)	50 in (130 cm)
Working Depth	4.5 in (11 cm)	5.5 in (14 cm)	5.5 in (14 cm)	NA
Max Flow	16 gpm (61 L/min)	16 gpm (61 L/min)	16 gpm (61 L/min)	16 gpm (61 L/min)
Max Pressure	3,000 psi (20 MPa)	3,625 psi (25 MPa)	3,625 psi (25 MPa)	NA
Carrier Pressure	NA	NA	NA	3,100 psi (21 MPa)
Weight	335 lb (152 kg)	584 lb (265 kg)	628 lb (285 kg)	608 lb (276 kg)

HARLEY RAKES (EUROPE ONLY)

MODEL	Harley Rake – D4M – Manual	Harley Rake – D4H3 – Dual Hydraulic
Model Number	UMA1300	UMA1305
Industry Part Number	22748M-0961-X	27748H3-0961-X
Width	55.4 in (141 cm)	55.4 in (141 cm)
Working Depth	48 in (122 cm)	48 in (122 cm)
Max Flow	15 gpm (57 L/min)	15 gpm (57 L/min)
Max Pressure	3,000 psi (20 MPa)	3,000 psi (20 MPa)
Angle Roll Degree	20°	20°
Weight	365 lb (166 kg)	380 lb (170 kg)



POWER RAKES

MODEL	Vermeer Power Rake Manual – UPR48	Vermeer Power Rake Hydraulic – UPR48	Vermeer Power Rake Manual – UPR60	Vermeer Power Rake Hydraulic – UPR60
Model Number	UMA1301	UMA1306	UMA1310	UMA1315
Width	56 in (140 cm)	56 in (140 cm)	68 in (170 cm)	68 in (170 cm)
Working Depth	48 in (122 cm)	48 in (122 cm)	68 in (170 cm)	68 in (170 cm)
Max Flow	18 gpm (68 L/min)	18 gpm (68 L/min)	18 gpm (68 L/min)	18 gpm (68 L/min)
Max Pressure	3,500 psi (24 MPa)	3,500 psi (24 MPa)	3,500 psi (24 MPa)	3,500 psi (24 MPa)
Angle Roll Degree	25°	25°	25°	25°
Weight	520 lb (235 kg)	520 lb (235 kg)	565 lb (255 kg)	565 lb (255 kg)





SOIL MOWERS

mini loader
attachment compatibility

SOIL MOWERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
MSSA305	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1331	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1333	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1336	X	X	✓	✓	✓	✓	✓	✓	✓

HARLEY RAKES

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1300	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1305	●	●	✓	✓	✓	✓	✓	✓	✓

POWER RAKES

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1301	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1306	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1310	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1315	X	X	✓	✓	✓	✓	✓	✓	✓

COMPATIBLE
 COMPATIBLE BUT NOT RECOMMENDED
 NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



SOIL MOWERS

MODEL	ATX530	ATX720	ATX850	ATX960
MSSA305	✓	●	✓	X
UMA1331	X	X	X	X
UMA1333	X	X	X	X
UMA1336	X	X	X	X

HARLEY RAKES

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1300	✓	✓	✓	X
UMA1305	●	●	●	X

POWER RAKES

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1301	✓	✓	✓	X
UMA1306	●	●	●	X
UMA1310	✓	✓	✓	X
UMA1315	●	●	●	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



GRAPPLES

specifications

Brush, limbs, logs and bulky debris can slow down a job. **Grapples** clamp onto loose, uneven material so operators can lift, carry and place it with more control than a standard bucket.



BRUSH GRAPPLES

MODEL	Vermeer Brush Grapple – UBG36	Vermeer Brush Grapple – UBG42	Vermeer Brush Grapple – UBG48	Vermeer Brush Grapple – UBG54	Vermeer Brush Grapple Dual – UBG54D
Model Number	UMA1423	UMA1426	UMA1429	UMA1432	UMA1433
Weight	355 lb (162 kg)	365 lb (166 kg)	415 lb (189 kg)	425 lb (193 kg)	545 lb (248 kg)
Width	36 in (91 cm)	42 in (107 cm)	48 in (122 cm)	54 in (137 cm)	54 in (137 cm)
Claw Opening	42 in (107 cm)	42 in (107 cm)	42 in (107 cm)	42 in (107 cm)	42 in (107 cm)
Max Capacity	1,245 lb (564 kg)	1,235 lb (560 kg)	1,185 lb (537 kg)	1,175 lb (532 kg)	1,055 lb (478 kg)
Hydraulic Cylinder	3,100 psi (21 MPa)	3,100 psi (21 MPa)	3,100 psi (21 MPa)	3,100 psi (21 MPa)	3,100 psi (21 MPa)

GRAPPLE BUCKETS

MODEL	Bradco Scrap Grapple Bucket – 36 in	Bradco Scrap Grapple Bucket – 42 in
Model Number	UMA1442	UMA1443
Industry Part Number	107480-X	107481-X
Weight	260 lb (120 kg)	280 lb (130 kg)
Width	36 in (91 cm)	42 in (107 cm)
Claw Opening	29 in (74 cm)	29 in (74 cm)
Hydraulic Cylinder	3,000 psi (20 MPa)	3,000 psi (20 MPa)



LOG GRAPPLES

MODEL	Berlon Forestry Claw – 60 in	Vermeer ULG46 – Fixed Log Grapple	Vermeer USLG46 – Swivel Log Grapple	Vermeer URLG46 – Hydraulic Rotating Log Grapple
Model Number	UMA1420	UMA1400	UMA1405	UMA1410
Industry Part Number	MIFC2	NA	NA	NA
Weight	261 lb (118 kg)	440 lb (200 kg)	375 lb (170 kg)	425 lb (193 kg)
Claw Opening	60 in (153 cm)	46 in (117 cm)	46 in (117 cm)	46 in (117 cm)
Max Capacity	2,000 lb (900 kg)	1,500 lb (680 kg)	1,500 lb (680 kg)	1,500 lb (680 kg)
Hydraulic Cylinder	3,000 psi (20 MPa)	3,000 psi (20 MPa)	3,000 psi (20 MPa)	3,000 psi (20 MPa)

ROOT GRAPPLES

MODEL	Vermeer Root Rake Grapple – URRG42	Vermeer Root Rake Grapple – URRG48	Vermeer Root Rake Grapple – URRG54
Model Number	UMA1413	UMA1417	UMA1419
Weight	395 lb (180 kg)	455 lb (207 kg)	480 lb (218 kg)
Width	42 in (107 cm)	48 in (122 cm)	54 in (137 cm)
Claw Opening	36 in (91 cm)	36 in (91 cm)	36 in (91 cm)
Max Capacity	1,205 lb (545 kg)	1,145 lb (520 kg)	1,120 lb (508 kg)
Hydraulic Cylinder	3,100 psi (21 MPa)	3,100 psi (21 MPa)	3,100 psi (21 MPa)





GRAPPLES

mini loader
attachment compatibility

BRUSH GRAPPLES

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1423	✓	✓	●	●	●	✓	✓	●	●
UMA1426	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1429	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1432	X	X	●	●	✓	●	●	✓	✓
UMA1433	X	X	●	●	✓	●	●	✓	✓

GRAPPLE BUCKETS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1442	✓	✓	✓	X	X	✓	✓	X	X
UMA1443	✓	✓	✓	X	X	✓	✓	X	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



LOG GRAPPLES

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1420	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1400	X	●	✓	✓	✓	✓	✓	✓	✓
UMA1405	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1410	✓	✓	✓	✓	✓	✓	✓	✓	✓

ROOT GRAPPLES

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1413	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1417	X	X	✓	✓	✓	✓	✓	✓	✓
UMA1419	X	X	✓	✓	✓	●	●	✓	✓

✓ COMPATIBLE

● COMPATIBLE BUT NOT RECOMMENDED

X NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



GRAPPLES

compact articulated loader
attachment compatibility

BRUSH GRAPPLES

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1423	●	●	●	X
UMA1426	✓	✓	✓	X
UMA1429	✓	✓	✓	X
UMA1432	●	●	✓	X
UMA1433	●	●	✓	X

GRAPPLE BUCKETS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1442	X	X	X	X
UMA1443	X	X	X	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



LOG GRAPPLES

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1420	✓	✓	✓	X
UMA1400	✓	✓	✓	X
UMA1405	✓	✓	✓	X
UMA1410	●	●	●	X

ROOT GRAPPLES

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1413	✓	✓	✓	X
UMA1417	✓	✓	✓	X
UMA1419	●	●	✓	X

✓ COMPATIBLE

● COMPATIBLE BUT NOT RECOMMENDED

X NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



DOZER BLADES

specifications

Dozer blades push soil, backfill trenches, level rough areas and clear loose material. They help crews handle common dirt work with compact equipment instead of relying as much on shovels, wheelbarrows and other hand tools.



DOZER BLADES

MODEL	Bradco Hydraulic Dozer Blade – 46 in	Bradco Hydraulic Dozer Blade w/Tilt – 46 in	Bradco Hydraulic Dozer Blade w/Tilt – 67 in
Model Number	UMA1250	UMA1255	UMA1260
Industry Part Number	104672-X	104571-X	105672-X
Weight	257 lb (117 kg)	257 lb (117 kg)	310 lb (140 kg)
Width	47 in (120 cm)	47 in (120 cm)	67 in (170 cm)
Height	17 in (43 cm)	17 in (43 cm)	17 in (43 cm)
Angle (Left to Right)	30°	30°	30°
Tilt (Left to Right)	0°	6°	6°
Hydraulic Cylinder	3,000 psi (20 MPa)	3,000 psi (20 MPa)	3,000 psi (20 MPa)



MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1250	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1255	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1260	●	●	✓	✓	✓	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1250	✓	✓	✓	X
UMA1255	✓	✓	✓	X
UMA1260	●	✓	✓	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



TRENCHERS

specifications

Irrigation lines, drainage work and utility runs start with a clean trench. **Trencher** attachments cut narrow paths through soil, helping crews install pipe, cable or conduit without bringing another dedicated machine to the job.



TRENCHERS

MODEL	Vermeer Trencher Attachment – UTR48	Vermeer Trencher Attachment – STR48
Model Number	UMA1450	MSSA500
Max Weight	640 lb (290 kg)	520 lb (240 kg)
Max Trench Depth	48 in (122 cm)	48 in (122 cm)
Max Trench Width	8 in (20 cm)	8 in (20 cm)
Max Flow	20 gpm (76 L/min)	16.5 gpm (62.5 L/min)
Max Pressure	3,100 psi (21 MPa)	3,000 psi (20 MPa)

CONCRETE MIXER

MODEL	Vermeer Concrete Mixer – UCM9
Model Number	UMA1460
Max Weight	520 lb (240 kg)
Max Trench Depth	48 in (122 cm)
Max Trench Width	8 in (20 cm)
Max Flow	16.5 gpm (62.5 L/min)
Max Pressure	3,000 psi (20 MPa)

CORE SAW

MODEL	Vermeer Core Saw – UCS418
Model Number	UMA1465
Max Weight	520 lb (240 kg)
Max Trench Depth	48 in (122 cm)
Max Trench Width	8 in (20 cm)
Max Flow	16.5 gpm (62.5 L/min)
Max Pressure	3,000 psi (20 MPa)



MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1450	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1460	✗	✗	✓	✓	✓	●	✓	✓	✓
UMA1465	✗	✗	✗	✗	✓	✗	✗	✓	✓
MSSA500	●	✗	✓	✓	✓	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1450	✓	●	✓	✗
UMA1460	●	●	✓	✗
UMA1465	✗	✗	✗	✗
MSSA500	✓	●	✗	✗



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



PLOWS

specifications and
attachment compatibility

Some installs call for less open-cut work. **Vibratory plows** pull pipe, cable or irrigation line underground with less trenching, making them a practical choice for utility, landscape and rental applications where ground disturbance matters.



PLOWS

MODEL	Vermeer SVP18 – Vibratory Plow Attachment
Model Number	MSSA600
Weight	340 lb (150 kg)
Max Plow Depth	12 in (30 cm)
Max Product Diameter Plowed	.75 in (19 mm)
Max Product Diameter Pulled	1.5 in (3.8 cm)
Max Flow	16.5 gpm (62.5 L/min)
Max Pressure	3,100 psi (21 MPa)

MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
MSSA600	●	●	✓	✓	✓	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
MSSA600	✓	●	X	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



Forks help crews lift, carry and place pallets, pavers, sod and jobsite supplies with compact equipment instead of moving them by hand. They help make loading, unloading and staging materials easier across the yard or jobsite.

FORKS

MODEL	Berlon Pallet Forks and Frame – 36 in	Berlon Pallet Forks and Frame – 42 in	Berlon Pallet Forks and Frame – 48 in
Model Number	UMA1500	UMA1505	UMA1510
Industry Part Number	MIPFF-36	MIPFF-42	MIPFF-48
Weight	260 lb (120 kg)	270 lb (122.5 kg)	280 lb (127 kg)
Fork Length	36 in (91 cm)	42 in (107 cm)	48 in (122 cm)
Frame Width	30.5 in (77.5 cm)	30.5 in (77.5 cm)	30.5 in (77.5 cm)
Rated Capacity	3,500 lb (1,600 kg)	3,500 lb (1,600 kg)	3,500 lb (1,600 kg)





MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1500	✓	✓	✓	✓	●	✓	✓	●	●
UMA1505	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1510	●	✓	✓	✓	✓	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1500	●	●	●	X
UMA1505	✓	✓	✓	X
UMA1510	✓	✓	✓	X



COMPATIBLE




COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.




After the tree comes down, the work is not over. **Stump cutters** remove remaining stump material, while **root cutters** can help with cleanup and site preparation before restoration, landscaping or replanting.

CUTTERS

MODEL	Vermeer Root Cutter – RC14	Vermeer Stump Cutter – USCA30
Model Number	MSSA715	UMA1700
Weight	550 lb (250 kg)	660 lb (300 kg)
Max Cutting Depth	14 in (36 cm)	12 in (30 cm)
Max Cutting Width	2.5 in (6.4 cm)	36 in (91 cm)
Max Cutting Height	NA	24.5 in (77.5 cm)
Min Flow	NA	12 gpm (45 L/min)
Max Flow	16.5 gpm (62.5 L/min)	17 gpm (64 L/min)
Max Pressure	3,045 psi (21 MPa)	3,100 psi (21 MPa)





MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
MSSA715	●	X	✓	✓	✓	✓	✓	✓	✓
UMA1700	X	X	●	✓	✓	●	●	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
MSSA715	✓	✓	X	X
UMA1700	X	X	X	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



Snow blades and **snow pushers** keep winter cleanup moving in driveways, parking lots, sidewalks and other tight spaces. Blades angle snow with control, while pushers carry larger volumes to help keep jobsites and properties clear.

SNOW TOOLS

MODEL	Berlon Snow Blade – 48 in	Berlon Snow Blade – 66 in	Berlon Snow Pusher – 60 in
Model Number	UMA1615	UMA1620	UMA1630
Industry Part Number	MISBLD-4	MISBLD-5.5	MISPLP-5
Weight	318 lb (144 kg)	353 lb (160 kg)	725 lb (329 kg)
Width	48 in (122 cm)	66 in (168 cm)	60 in (153 cm)
Height	22 in (56 cm)	22 in (56 cm)	34 in (86 cm)

MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1615	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1620	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1630	X	X	●	✓	✓	●	●	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1615	✓	✓	✓	X
UMA1620	✓	✓	✓	X
UMA1630	●	●	✓	X



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



Hard surfaces can slow prep, repair and demolition work. **Breaker and boring tools** pair with compact equipment to break material in confined jobsites, giving crews another attachment option before removal or

BORING TOOLS

MODEL	Vermeer Hydraulic Boring Attachment (MCL)	Vermeer Hydraulic Breaker Attachment (MCL)
Model Number	MSSA605	UMA1470
Industry Part Number	MC4500MS	NA
Weight	115 lb (52.2 kg)	100 lb (45.4 kg)
Max Boring Diameter	4.5 in (11 cm)	4.5 in (11 cm)
Max Torque	530 ft-lb (720 Nm)	600 ft-lb (813.5 Nm)
Max Flow	NA	8 gpm (30 L/min)
Max Pressures	NA	3,100 psi (21 MPa)

BREAKERS

MODEL	Vermeer Hydraulic Breaker Attachment
Model Number	MSSA700
Industry Part Number	HP200 FS
Weight	250 lb (110 kg)
Max Energy	200 lb-ft (271 Nm)
Steel Diameter	1.8 in (4.6 cm)

MINI LOADERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
MSSA605	●	●	✓	✓	✓	✓	✓	✓	✓
MSSA700	●	●	✓	✓	✓	✓	✓	✓	✓
UMA1470	X	X	X	X	X	✓	✓	✓	✓

COMPACT ARTICULATED LOADERS

MODEL	ATX530	ATX720	ATX850	ATX960
MSSA605	✓	●	✓	X
MSSA700	✓	●	✓	X
UMA1470	✓	✓	✓	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



Rotary brooms and land levelers help crews get the ground ready before planting, seeding or sodding. Brooms sweep aside loose material, while land levelers smooth rough spots so the surface is ready for the next step.

BROOMS

MODEL	Sweepster Rotary Broom – Manual (Europe Only)	Vermeer Angle Broom Manual – UAB48	Vermeer Angle Broom Manual – UAB60
Model Number	UMA1275	UMA1276	UMA1280
Industry Part Number	22641MM-0961-X	NA	NA
Weight	145 lb (65.8 kg)	495 lb (225 kg)	530 lb (240 kg)
Width	42 in (107 cm)	48 in (122 cm)	60 in (152 cm)
Max Flow	16 gpm (61 L/min)	18 gpm (68 L/min)	18 gpm (68 L/min)
Max Pressure	3,000 psi (20 MPa)	3,500 psi (24 MPa)	3,500 psi (24 MPa)

LAND LEVELERS

MODEL	Vermeer Land Leveler – ULL48	Vermeer Land Leveler w/Ripper – ULL48
Model Number	UMA1201	UMA1202
Width	48.25 in (122 cm)	55.4 in (140 cm)
Weight	173 lb (79 kg)	231 lb (105 kg)
Digging Depth	NA	4.2 in (11 cm)
Shank Quantity	0	6

MISCELLANEOUS ATTACHMENTS

MODEL	Bradco Tree Fork	Bradco Mini Tilt	Fecon Stump Screw – SHX12
Model Number	UMA1210	UMA1225	NA
Industry Part Number	19938-X	100145-X	SHX12
Weight	145 lb (65.8 kg)	94 lb (43 kg)	400 lb (200 kg)
Width	25 in (64 cm)	NA	NA
Tilt	NA	18	NA
Max Flow	NA	NA	10 gpm - 20 gpm (38 L/min - 76 L/min)
Max Pressure	3,000 psi (20 MPa)	NA	3,000 psi (20 MPa)
Max Torque	NA	NA	4,000 ft-lb (5,000 Nm)
Tine Length	33 in (84 cm)	NA	NA
Fork Range of Motion	23 in (58 cm)	NA	NA
Bit Diameter	NA	NA	12 in (30 cm)



MISCELLANEOUS PRODUCTS

BROOMS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1275	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1276	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1280	✓	✓	✓	✓	✓	✓	✓	✓	✓

LAND LEVELERS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1201	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1202	✓	✓	✓	✓	✓	✓	✓	✓	✓

MISCELLANEOUS ATTACHMENTS

MODEL	CTX50	S450TX	S925TX	CTX100	CTX160	ML80	ML100	ML130	ML150
UMA1210	✓	✓	✓	✓	✓	✓	✓	✓	✓
UMA1225	✓	✓	✓	✓	✓	✓	✓	✓	✓
SHX12	X	X	✓	✓	✓	✓	✓	✓	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.

MISCELLANEOUS PRODUCTS

compact articulated
loader attachment
compatibility

BROOMS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1275	✓	●	✓	X
UMA1276	✓	●	✓	X
UMA1280	✓	●	✓	X

LAND LEVELERS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1201	✓	✓	✓	X
UMA1202	✓	✓	✓	X

MISCELLANEOUS ATTACHMENTS

MODEL	ATX530	ATX720	ATX850	ATX960
UMA1210	✓	●	✓	X
UMA1225	✓	●	✓	X
SHX12	X	X	X	X

 COMPATIBLE
  COMPATIBLE BUT NOT RECOMMENDED
  NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.

FULL-SIZE ATTACHMENTS



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

COMPATIBLE: The attachment is compatible with the associated base unit. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

COMPATIBLE BUT NOT RECOMMENDED: The attachment is technically compatible but not recommended for combined use with the associated base unit. Functionality, reliability or performance may be limited; damage to or excess wear and tear on the attachment or base unit is possible. Note that use of attachments that are not recommended by Vermeer and that (in the sole judgment of Vermeer) amounts to abnormal use, misuse or negligence will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.

NOT AUTHORIZED: The attachment is not authorized for use with the associated base unit. Combined use may be technically infeasible or pose unacceptable risk of harm to property or persons. Never operate these attachments and base units in combination. Note that use of these attachments, in addition to being unsafe, will void the Vermeer Limited Warranty for both the Vermeer base unit and Vermeer attachment. Consult your operator's manual or Vermeer dealer for additional information about attachment compatibility.



UTILITY BUCKETS

MODEL	Berlon Utility Bucket – 48 in	Berlon Utility Bucket – 54 in	Berlon Utility Bucket – 60 in	Berlon Utility Bucket – 66 in
Model Number	FSA1000	FSA1005	FSA1010	FSA1015
Industry Part Number	UT-48	UT-54	UT-60	UT-66
Inside Dimension	48 in (122 cm)	54 in (137 cm)	60 in (153 cm)	66 in (168 cm)
Outside Dimension	49.5 in (126 cm)	55.5 in (141 cm)	61.5 in (156 cm)	67.5 in (171 cm)
Height	21 in (53 cm)	21 in (53 cm)	21 in (53 cm)	21 in (53 cm)
Depth	33 in (84 cm)	33 in (84 cm)	33 in (84 cm)	33 in (84 cm)
Weight	353 lb (160 kg)	385 lb (175 kg)	406 lb (184 kg)	431 lb (195 kg)

TOOTH BUCKETS

MODEL	Berlon HD Tooth Bucket – 48 in	Berlon HD Tooth Bucket – 54 in	Berlon HD Tooth Bucket – 60 in	Berlon HD Tooth Bucket – 66 in
Model Number	FSA1020	FSA1025	FSA1030	FSA1035
Industry Part Number	UT-48WET2	UT-54WET2	UT-60WET2	UT-66WET2
Inside Dimension	48 in (122 cm)	54 in (137 cm)	60 in (153 cm)	66 in (168 cm)
Outside Dimension	49.5 in (126 cm)	55.5 in (141 cm)	61.5 in (156 cm)	67.5 in (171 cm)
Height	21 in (53 cm)	21 in (53 cm)	21 in (53 cm)	21 in (53 cm)
Depth	33 in (84 cm)	33 in (84 cm)	33 in (84 cm)	33 in (84 cm)
Weight	360 lb (160 kg)	400 lb (181 kg)	426 lb (193 kg)	451 lb (205 kg)
Heaped Capacity	12.8 ft³ (.362 m³)	14.4 ft³ (.408 m³)	16 ft³ (.453 m³)	17.6 ft³ (.498 m³)

HIGH VOLUME BUCKETS

MODEL	Berlon High Volume Bucket – 60 in	Berlon High Volume Bucket – 66 in	Berlon High Volume Bucket – 72 in
Model Number	FSA1040	FSA1045	FSA1050
Industry Part Number	HVMB-60	HVMB-66	HVMB-72
Inside Dimension	60 in (153 cm)	66 in (168 cm)	72 in (183 cm)
Outside Dimension	61.5 in (156 cm)	67.5 in (171 cm)	73.5 in (187 cm)
Height	29 in (74 cm)	29 in (74 cm)	29 in (74 cm)
Depth	39 in (99 cm)	39 in (99 cm)	39 in (99 cm)
Weight	510 lb (230 kg)	553 lb (251 kg)	573 lb (260 kg)
Heaped Capacity	27.5 ft³ (.779 m³)	30.2 ft³ (.885 m³)	33.1 ft³ (.937 m³)



UTILITY BUCKETS

MODEL	ATX960
FSA1000	✓
FSA1005	✓
FSA1010	✓
FSA1015	✓

TOOTH BUCKETS

MODEL	ATX960
FSA1020	✓
FSA1025	✓
FSA1030	✓
FSA1035	✓

HIGH VOLUME BUCKETS

MODEL	ATX960
FSA1040	✓
FSA1045	✓
FSA1050	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED

✗ NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



GRAPPLES

specifications

LIGHT DUTY GRAPPLES

MODEL	Berlon Light Duty Grapple – 54 in Single Claw	Berlon Light Duty Grapple – 60 in Single Claw	Berlon Light Duty Grapple – 66 in Single Claw	Berlon Light Duty Grapple – 66 in Dual Claw	Berlon Light Duty Grapple – 72 in Dual Claw
Model Number	FSA1425	FSA1430	FSA1435	FSA1440	FSA1445
Industry Part Number	LDGR54	LDGR-60	LDGR-66	MDGR-66	MDGR-72
Weight	491 lb (223 kg)	524 lb (238 kg)	557 lb (253 kg)	735 lb (333 kg)	770 lb (350 kg)
Claw Opening	41 in (100 cm)	41 in (100 cm)	41 in (100 cm)	41 in (100 cm)	41 in (100 cm)
Max Capacity	2,000 lb (900 kg)	2,000 lb (900 kg)	2,000 lb (900 kg)	2,500 lb (1,100 kg)	2,500 lb (1,100 kg)
Hydraulic Cylinder	2,500 psi (17 MPa)	2,500 psi (17 MPa)	2,500 psi (17 MPa)	2,500 psi (17 MPa)	2,500 psi (17 MPa)

LOG GRAPPLES

MODEL	Vermeer FSLG54 – Swivel Log Grapple	Vermeer FRLG54 – Hydraulic Rotating Log Grapple
Model Number	FSA1405	FSA1410
Weight	680 lb (310 kg)	750 lb (340 kg)
Claw Opening	54 in (137 cm)	54 in (137 cm)
Max Capacity	2,700 lb (1,200 kg)	2,700 lb (1,200 kg)
Hydraulic Cylinder	3,100 psi (21 MPa)	3,100 psi (21 MPa)

FORESTRY CLAW

MODEL	Berlon Forestry Claw – 60 in
Model Number	FSA1420
Industry Part Number	BFC
Weight	261 lb (118 kg)
Claw Opening	60 in (153 cm)
Max Capacity	2,000 lb (900 kg)
Hydraulic Cylinder	2,500 psi (17 MPa)



LIGHT DUTY GRAPPLES

MODEL	ATX960
FSA1425	✓
FSA1430	✓
FSA1435	✓
FSA1440	✓
FSA1445	✓

LOG GRAPPLES

MODEL	ATX960
FSA1405	✓
FSA1410	✓

FORESTRY CLAW

MODEL	ATX960
FSA1420	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



TRENCHERS

specifications and
attachment compatibility

TRENCHER

MODEL

Vermeer Trencher Attachment – FTR48

Model Number

FSA1455

Max Weight

700 lb (300 kg)

Max Trench Depth

48 in (122 cm)

Max Trench Width

8 in (20 cm)

Max Flow

25 gpm (95 L/min)

Max Pressure

3,100 psi (21 MPa)

TRENCHER

MODEL

ATX960

FSA1455



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.



PALLET FORKS (RAIL STYLE)

MODEL	Berlon Class II Pallet Forks – Rail Style 48 in	Berlon Class II Pallet Forks – Rail Style 54 in
Model Number	FSA1500	FSA1505
Industry Part Number	BPFF-48-2	BPFF-54
Weight	415 lb (188 kg)	434 lb (197 kg)
Fork Length	48 in (122 cm)	54 in (137 cm)
Rated Capacity	4,000 lb (2,000 kg)	5,500 lb (2,500 kg)

SQUARE BALE SPEAR

MODEL	Berlon Square Bale Spear – 52 in
Model Number	FSA1700
Industry Part Number	BSC-3324
Weight	182 lb (82.6 kg)
Width	52 in (130 cm)
Height	39 in (99 cm)
Bottom Tines	3

MANURE FORKS

MODEL	Berlon Manure Fork – 54 in	Berlon Manure Forks – 60 in
Model Number	FSA1710	FSA1715
Industry Part Number	MTMF-54	MTMF-60
Weight	329 lb (149 kg)	362 lb (164 kg)
Fork Length	54 in (137 cm)	60 in (153 cm)
Replaceable Tines	9	10



PALLET FORKS (RAIL STYLE)

MODEL	ATX960
FSA1500	✓
FSA1505	✓

MANURE FORKS

MODEL	ATX960
FSA1710	✓
FSA1715	✓

SQUARE BALE SPEAR

MODEL	ATX960
FSA1700	✓



COMPATIBLE



COMPATIBLE BUT NOT RECOMMENDED



NOT AUTHORIZED

The information and specifications set forth herein are for informative purposes only. Vermeer makes no warranties herein and Vermeer explicitly disclaims any express, implied or statutory warranty including, but not limited to, any warranty of merchantability or fitness for a particular purpose. Please see the color key at the beginning or end of this brochure for more information about attachment use and compatibility.

Vermeer[®]



EQUIPPED TO DO MORE.[®]

Vermeer Corporation

1210 Vermeer Road East
Pella, Iowa 50219
800-370-3659

vermeer.com

Vermeer Corporation and MultiOne SRL Corporation reserve the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Mini skid steer attachments available from Vermeer dealers may be manufactured by Vermeer Corporation or other attachment manufacturers. Please contact your local Vermeer dealer for more information on machine specifications and attachments.

Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. All other trademarks, registered trademarks and service marks are the property of their respective owners.

© 2026 Vermeer Corporation. All Rights Reserved.